



### Features:

#### EUROLITE LED PLL-480 QCL Panel

DMX-controlled surface light with 480 4in1 RGBW LEDs

- Frost filter provides a soft, homogeneous light
- 4 barn doors to avoid blinding the audience and for protection during transport
- Slim, rugged metal housing
- Stand or truss installation
- 480 LEDs SMD 5050 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; pulse-width modulation variable
- Strobe effect
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; master/slave function
- Fixtures available for Light J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
- Flicker-free
- With a beam angle of 120°
- With mounting bracket
- LCD display
- Rugged carrying handle
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; wedding/gala/events; Trade fair and shop fitting; theater; rental; video and photography
- Silent operation
- Application possibility: Suspended; on stand

### Logistic

EAN / GTIN: 4026397694598

Weight: 41,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

## ROADINGER Flightcase 2x LED PLL-480

- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Branded hardware

### Technical specifications:

---

Weight: 37.50 kg

---

#### EUROLITE LED PLL-480 QCL Panel

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	205 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Fuse:	T 6.3 A fuse fix in power supply
Lamp type:	LED lamp
LED type:	480 x SMD 5050 4in1 QCL RGBW (homogenous color mix)
Flash rate:	1 - 19 Hz
DMX channels:	6; 4
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; master/slave function
Fixtures available for:	Light J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	120°
Beam angle (1/2 peak):	120°
Illuminance in Lux (lx):	Red (R) 1m: 438 lx, 3m: 61 lx, 6m: 18 lx Green (G) 1m: 633 lx, 3m: 88 lx, 6m: 25 lx Blue (B) 1m: 209 lx, 3m: 29 lx, 6m: 8 lx Cold white (CW) 1m: 2130 lx, 3m: 296 lx, 6m: 87 lx All 1m: 2696 lx, 3m: 380 lx, 6m: 112 lx
Lamp life:	50000 h
Luminous flux:	17103 lm
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display

Carrying handle:	1 pc/pcs
Material:	Metal; aluminum casting
Dimensions:	Width: 64 cm Depth: 13 cm Height: 33.5 cm
Weight:	12.60 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	F
EPREL-Nr:	1243720
Diameter mounting holes:	3 x Ø12mm
Material:	Metal, 3 mm
Material:	Metal, 1.5 mm

### **ROADINGER Flightcase 2x LED PLL-480**

Maximum load:	50 kg
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Inside dimensions:	64 cm x 38.5 cm x 29 cm
Device compartment:	64 cm x 14 cm x 29 cm
Accessory compartment:	64 cm x 10.5 cm x 29 cm
Dimensions:	Length: 70 cm Width: 47 cm Height: 39 cm
Weight:	12.30 kg

### **Scope of delivery:**

- 1 x spotlight
- 1 x power cord
- 1 x plug (male)
- 1 x user manual