



Features:

- Positioning within
- <p>EUROLITE LED TMH-S60 Moving Head Spot
- <h2 class="featureSatz">Compact moving head Spot with 60 W LED, gobos and color wheel</h2>3 gobos with heart patterns for exchange included
- 1 LED 60 W COB (chip-on-board) cold white (CW)
- Positioning within 540° PAN, 180° TILT
- Gobo wheel with rotating gobos; focus manual; color wheel
- Dimmer electronic
- Beam effect; strobe effect
- Color wheel with 7 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 7 gobos and open
slot-in gobo system for easy gobo replacement
- Shake effect
- 4 integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); QuickDMX via USB (optional)
- Fixtures available for LED PC-Control 512; EASY SHOW 1; Light Captain
- Flicker-free
- With a beam angle of 12°
- 4 digit 7-segment LED display
- Rubber feet
- For application areas such as: Clubs/dancing school; wedding/gala/events; party room; mobile djs / entertainer; restaurants, bars and hotels

Logistic

EAN / GTIN: 4026397716429

Weight: 30,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

- Application possibility: Standing; suspended
- <p>ROADINGER Flightcase 4x LED TMH-13/17/S30/W36 with wheels
- <h2 class="featureSatz">Trunk case with castors</h2>High-quality workmanship with plywood multi-layer glued 7 mm, black, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function
- Castors

Technical specifications:

Weight:	25.50 kg
---------	----------

EUROLITE LED TMH-S60 Moving Head Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	95 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Device fuse:	5 x 20 mm, T 1.5 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 60 W COB (chip-on-board) cold white (CW)
Max. TILT movement:	180° positioning
Max. PAN movement:	540° positioning
Flash rate:	1.5 - 23 Hz
Equipment:	Gobo wheel with rotating gobos; focus manual; color wheel
Color generation:	Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with rotating gobos, 7 gobos and open Outside diameter 13.8mm Image diameter 11mm Slot-in gobo system for easy gobo replacement Shake effect
DMX channels:	10; 12
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function; CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); QuickDMX via USB (optional)
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; Light Captain

Projection:	Flicker-free
PWM frequency:	2800 Hz
Beam angle:	12°
Beam angle (1/2 peak):	12°
Color temperature:	7700K
Illuminance in Lux (lx):	Cold white (CW) 1m: 15205 lx, 3m: 1764 lx, 6m: 445 lx
Housing color:	Black
Display type:	4 digit 7-segment LED display
Transport aid:	Rubber feet
Dimensions:	Width: 17.0 cm Depth: 15.0 cm Height: 24.0 cm
Weight:	3.15 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x LED TMH-13/17/S30/W36 with wheels

Maximum load:	50 kg
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs with shut-off function
Transport aid:	Castors
Material:	Plywood multi-layer glued, 7 mm
Color:	Black, laminated
Device compartment:	18 cm x 15.5 cm x 29 cm
Accessory compartment:	10 cm x 15.5 cm x 29 cm
Inside dimensions:	49 cm x 32.5 cm x 29 cm
Dimensions:	Width: 55 cm Depth: 38 cm Height: 47 cm
Weight:	12.90 kg

Scope of delivery:

1 x moving light
1 x user manual
1 x power cord
1 x omega bracket
1 x safety eyelet
3 x gobos