



### Features:

#### EUROLITE LED B-40 HCL Beam Effect MK2 wh

LED beam effect with RGBWA+UV color mixing, incl. remote-control

- 5 LEDs 10 W 6in1 HCL RGBWA/UV<BR> segments controlled separately
- Color blend stepless; Dimmer electronic; Rotation speed stepless
- Multi beam effect; strobe effect
- 8 integrated show programs
- The device is cooled by passive convection cooling
- Control via IR remote control; stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); master/slave function
- Fixtures available for Light´J; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- With omega bracket
- Monochrome 4 digit 7-segment LED display
- For application areas such as: Clubs/dancing school; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; advertisement/Shop window
- Application possibility: Standing; suspended

#### ROADINGER Flightcase 1x B-40 HCL/Laser

Trunk case, HIGHLINE version

- High-quality workmanship with birch multiplex 6.5 mm, dark brown
- Interior with foam padding
- Aluminum profile frames 20mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks

### Logistic

EAN / GTIN: 4026397718393

Weight: 15,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

- 2 high-quality spring locks
- Branded hardware
- European engineering
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

---

Weight: 10.72 kg

---

### EUROLITE LED B-40 HCL Beam Effect MK2 wh

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	56 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Fuse:	T 1.6 A fuse replaceable
Lamp type:	LED lamp
LED type:	5 x 10 W 6in1 HCL RGBWA/UV
Flash rate:	0.6 - 12 Hz
DMX channels:	3; 12; 23
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	IR remote control; stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); master/slave function
Fixtures available for:	Light J; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Housing color:	White
Attachment system:	Omega bracket
Display type:	Monochrome 4 digit 7-segment LED display
Dimensions:	Length: 32.00 cm Width: 32.00 cm Height: 39.00 cm
Weight:	4.22 kg
Noise classification:	Class 2 (slight noise)
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

**ROADINGER Flightcase 1x B-40 HCL/Laser**

Maximum load:	25 kg
Aluminum profile frames:	20 mm
Case handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Spring lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 6.5 mm, laminated
Color:	Dark brown
Device compartment:	32.5 cm x 32.5 cm x 39 cm
Dimensions:	Length: 40 cm Width: 40 cm Height: 48 cm
Weight:	6.50 kg

**Scope of delivery:**

- 1 x light effect
- 1 x user manual
- 1 x power cord
- 1 x omega bracket
- 4 x screw
- 4 x washer
- 1 x remote control
- 1 x battery