



List price: 1069.81 €

incl. 19% VAT.

Features:

EUROLITE LED Silent Par 6 QCL floor bk

LED floor spot with RGB/WW color mixing

- 14350 lux at 1 m
- 6 powerful LEDs 8 W 4in1 QCL RGB/WW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- Direct color selection for 25 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; QuickDMX via USB (optional); Master/slave function; Sound to light via Microphone
- Flicker-free
- With a beam angle of 16°
- With double bracket; with panning and tilting mounting bracket for ceiling or wall installation in most varying angles
- 4 digit 7-segment LED display
- Preprogrammed in Light´J; Light Captain
- For application areas such as: Clubs/dancing school; Wedding/gala/events; Trade fair and shop fitting; Stage; theater; restaurants, bars and hotels; mobile djs / entertainer
- Silent operation
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x xLR cable

Logistic

EAN / GTIN: 4026397728224

Weight: 20,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

ROADINGER Flightcase 4x SILENT PAR 6 QCL FLOOR

PRO flightcase for 4 x SILENT PAR 6 QCL FLOOR

- High-quality workmanship with birch multiplex 7 mm, black
- Interior with felt cover
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 3 hinged, chromium plated case handles
- Branded hardware
- 4 rubber feet
- Made in Europe

Technical specifications:

Weight: 17,20 kg

EUROLITE LED Silent Par 6 QCL floor bk

| | |
|-------------------------|-------------------------------------------------------------------------------------------------------------------|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 45 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug |
| Power output: | P-Con (gray), mounting version |
| LED: | 6 x 8 W 4in1 QCL RGB/WW (homogenous color mix) |
| Flash rate: | 0 - 20 Hz |
| DMX channels: | 6; 11 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; DMX; QuickDMX via USB (optional); Master/slave function; Sound to light via Microphone |
| Preprogrammed in: | Light J; Light Captain |
| Projection: | Flicker-free |
| Beam angle: | 16° |
| Beam angle (1/2 peak): | 16° |
| Beam angle (1/10 peak): | 29° |
| Housing color: | Black |
| Attachment system: | Double bracket Panning and tilting mounting bracket for ceiling or wall installation in most varying angles |
| Display type: | 4 digit 7-segment LED display |
| Dimensions: | Length: 14,3 cm Width: 17,7 cm Height: 21,1 cm |

| | |
|-----------------------|----------------------------------------------|
| Weight: | 2,15 kg |
| Noise classification: | Class 0 (no noise at all) |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase 4x SILENT PAR 6 QCL FLOOR

| | |
|--------------------------|-------------------------------------------------|
| Aluminum profile frames: | 30 mm |
| Case handle: | 3 pc/pcs |
| Transport aid: | 4 x rubber feet |
| Use of brands: | Branded hardware |
| Material: | Birch multiplex, 7 mm |
| Color: | Black |
| Device compartment: | 15 cm x 14 cm x 20 cm |
| Accessory compartment: | 11 cm x 30 cm x 21 cm |
| Inside dimensions: | 44 cm x 30 cm x 21 cm |
| Dimensions: | Width: 48,5 cm Depth: 35 cm Height: 30 cm |
| Weight: | 8,60 kg |