



Features:

EUROLITE AKKU MBT-3 Spot MK2

Light fan for special uplight and beam effects with rechargeable battery

- Cordless, flexible and versatile
- Battery operation up to 16h depending on program used
- Integrated automatic charging of the battery and status indicator
- 3 LEDs 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
 LEDs controlled separately
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) with adjustable response
- Strobe effect; fan effect; uplight effect
- 9 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; master/slave function; sound to light via microphone; IR remote control; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for Light´J; Light Captain; EASY SHOW 1; EASY SHOW 3; EASY SHOW 2; Colorchief
- Flicker-free
- Space-saving construction
- With a beam angle of 13°
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels; rental
- Silent operation

Logistic

EAN / GTIN: 4026397684087

- Application possibility: Standing; suspended

EUROLITE SB-15 Soft Bag

Universal softbag

- High-quality workmanship with nylon , black
- Interior with foam padding
- 2 carrying straps

Technical specifications:

| | |
|---------|---------|
| Weight: | 8.57 kg |
|---------|---------|

EUROLITE AKKU MBT-3 Spot MK2

| | |
|-------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Cable length: | 1.5 m |
| Power output: | IEC connector (F) mounting version |
| Fuse: | 5 x 20 mm, T 1.6 A fuse replaceable |
| Battery pack type: | 1 x lithium ion 14.8 V, 6600 mAh, 97.68 Wh |
| Battery pack: | Battery operation up to 16h depending on program used Recharging time 4h |
| Battery: | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| Lamp type: | LED lamp |
| LED type: | 3 x 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix) |
| Inclination angle: | 180 ° |
| Flash rate: | 0 - 25 Hz |
| DMX channels: | 3; 4; 8; 12; 16 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; master/slave function; sound to light via microphone; IR remote control; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Fixtures available for: | Light´J; Light Captain; EASY SHOW 1; EASY SHOW 3; EASY SHOW 2; Colorchief |
| Projection: | Flicker-free |
| Setup: | Space-saving construction |

| | |
|------------------------|---|
| Beam angle: | 13° |
| Beam angle (1/2 peak): | 13° |
| Housing color: | Black |
| Display type: | 4 digit 7-segment LED display |
| Dimensions: | Length: 30.5 cm Width: 9.5 cm Height: 22 cm |
| Weight: | 4.15 kg |
| Noise classification: | Class 0 (no noise at all) |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

EUROLITE SB-15 Soft Bag

| | |
|-----------------|---|
| Carrying strap: | 2 pc/pcs |
| Material: | Nylon |
| Color: | Black |
| Dimensions: | Width: 34.5 cm Depth: 21.5 cm Height: 22 cm |
| Weight: | 0.27 kg |

Scope of delivery:

2 x EUROLITE AKKU MBT-3 Spot MK2

- 1 x device
- 1 x power cord
- 1 x user manual
- 1 x remote control
- 1 x battery

1 x EUROLITE SB-15 Soft Bag

- 1 x bag
- 1 x segment