



Features:

EUROLITE AKKU IP PAR 7 QCL CRMX MK2

IP65 battery-powered spotlight with RGBW LEDs, CRMX, frost filters and IR remote control

- Integrated wireless receiver for CRMX operation
- Two additional frost filters provide a soft, homogeneous light
- Battery operation up to 9h depending on program used
- 7 LEDs 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
- Emergency lighting function in case of power failure; color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) with adjustable response; white balance; Energy-saving mode
- Strobe effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; master/slave function; IR remote control; DMX; W-DMX by wireless solution; CRMX by LumenRadio; RDM
- Fixtures available for Light J; Light Captain; Colorchief
- Flicker-free
- With a beam angle of 6°
- With double bracket
- OLED display
- Display of the remaining battery life for the current setting
- Charge status indicator
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- With pressure compensation membrane
- With a KENSINGTON LOCK theft protection

Logistic

EAN / GTIN: 4026397748253

Weight: 22,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

- For application areas such as: Architecture; stage; wedding/gala/events; rental; video and photography
- Silent operation
- Application possibility: Standing; suspended; on stand
- 3 buttons on the remote control for saving your own settings

ROADINGER Flightcase 4x AKKU IP PAR 7 QCL WDMX with charging function

Trunk case with castors

- With accessory compartment
- With 4 device compartments
- High-quality workmanship with plywood multi-layer glued 9 mm, black, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function
- 4 x castors with 2 locking brakes Ø 100 mm
- 4 x built-in stacking trays in the cover

Technical specifications:

Weight: 21.44 kg

EUROLITE AKKU IP PAR 7 QCL CRMX MK2

| | |
|-------------------------|------------------------------------------------------------------------------------------------------------------------|
| Power supply: | 100-240 V AC, 50/60 Hz |
| IP classification: | IP65 |
| Protection class: | Protection class I |
| Power connection: | Battery/battery pack Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided) |
| Cable length: | Approx. 1.2 m |
| Power output: | 1 x IP T-Con (F) mounting version |
| Battery pack: | Battery operation up to 9h depending on program used Recharging time 4h |
| Lamp type: | LED lamp |
| LED type: | 7 x 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix) |
| Flash rate: | 1 - 23 Hz |
| DMX channels: | 3; 4; 6; 8; 11 |
| DMX input: | 1 x 3-pin XLR (M) mounting version IP |
| DMX output: | 1 x 3-pin XLR (F) mounting version IP |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; master/slave function; IR remote control; DMX; W-DMX by wireless solution; CRMX by LumenRadio; RDM |
| Fixtures available for: | Light J; Light Captain; Colorchief |
| Projection: | Flicker-free |

| | |
|-------------------------|----------------------------------------------------------|
| Carrier frequency: | 2.4 GHz |
| Beam angle: | 6° |
| Beam angle (1/2 peak): | 6° Frost filter 13° Frost filter 20° |
| Beam angle (1/10 peak): | 16° Frost filter 32° Frost filter 44° |
| Housing color: | Black |
| Attachment system: | Double bracket |
| Display type: | OLED display |
| Display: | Battery runtime calculation , charge status indicator |
| Color: | Black |
| Theft protection: | KENSINGTON LOCK |
| Dimensions: | Width: 23.4 cm Height: 28.0 cm Diameter: Ø 17.0 cm |
| Weight: | 5.30 kg |
| Noise classification: | Class 0 (no noise at all); Class 0 (no noise at all) |
| Battery: | 1 x button cell 3.0 V CR2032 lithium manganese built-in |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase 4x AKKU IP PAR 7 QCL WDMX with charging function

| | |
|--------------------------|---------------------------------------------------------------------------------------------|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power connection: | Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided) |
| Device fuse: | 5 x 20 mm, F 5 A fuse replaceable |
| Aluminum profile frames: | 25 mm |
| Case handle: | 4 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs with shut-off function |
| Transport aid: | 4 x castors with 2 locking brakes Ø 100 mm 4 x built-in stacking trays in the cover |
| Material: | Plywood multi-layer glued, 9 mm |
| Color: | Black, laminated |
| Device compartment: | 18 cm x 25 cm x 26 cm |
| Accessory compartment: | 11.5 cm x 51.5 cm x 27 cm |
| Dimensions: | Width: 64 cm Depth: 56.5 cm Height: 49.5 cm |
| Weight: | 19.50 kg |
| Cable construction: | 3 x 1.5 mm ² H07RN-F |
| Cable length: | 1.2 m |

Scope of delivery:

4 x EUROLITE AKKU IP PAR 7 QCL CRMX MK2

- 1 x device
- 1 x user manual
- 1 x power cord
- 1 x remote control
- 1 x battery
- 2 x frost filter
- 2 x knurled screw
- 1 x declaration of conformity
- 2 x mounting bracket

1 x ROADINGER Flightcase 4x AKKU IP PAR 7 QCL WDMX with charging function

- 1 x case
- 4 x castors
- 16 x screw
- 1 x key
- 1 x user manual
- 1 x power cord