



**List price: 7971.81 €**

incl. 19% VAT.

### Features:

#### FUTURELIGHT EYE-740 MK2 QCL Zoom LED Moving Head Wash

PRO Washlight with 40 W Osram Ostar RGBW LEDs, large zoom range and pixel control

- 7 powerful LEDs 40 W 4in1 QCL RGBW (homogenous color mix) LEDs controlled separately
- Compact lightweight
- Variable color temperature 2800 K - 10000 K
- Crossfade channel from any color to white
- Number of scenes can be changed individually
- Positioning within 540° PAN and 210° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Exact 16 bit resolution at Dimmer, color, zoom
- The device is cooled by temperature-controlled fan
- Control via stand-alone; Master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by LumenRadio upgradeable; RDM; Sound to light via Microphone
- Flicker-free
- With a beam angle of 1° - 48°
- Multicolor LCD display, with battery buffering for easy controlling upgradeable
- Zoom motor-driven
- Patterns animated; foreground color adjustable; background color adjustable; dimmer curves with adjustable response; pulse-width modulation variable; pulse effect adjustable; white balance; scenes user-definable; CTO correction filter virtual; Dim to warm; colors preset; Dimmer speed (step response) adjustable
- Strobe effect
- Very quiet working noise

### Logistic

EAN / GTIN: 4026397695748

Weight: 78,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

- OSRAM LED installed
  - Preprogrammed in Light Captain
  - With Omega bracket
  - Rubber feet
  - Mains input and output for power linking up to 8 units
  - For application areas such as: Wedding/gala/events; Stage; theater; Rental
  - Application possibility: Standing; suspended
- Package contents**
- 1 x moving light, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x xLR cable

### ROADINGER Flightcase 4x EYE-740 MK2 with wheels

Trunk case with castors

- With 4 Device compartments
- With 1 accessory compartment
- High-quality workmanship with plywood multi-layer glued 7 mm, black, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes

### Technical specifications:

---

Weight: 76,90 kg

---

### FUTURELIGHT EYE-740 MK2 QCL Zoom LED Moving Head Wash

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	210 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Power output:	IP T-Con (F) mounting version
Device fuse:	5 x 20 mm, T 2 A Fuse replaceable
Lamp type:	LED lamp
LED:	7 x 40 W 4in1 QCL RGBW (homogenous color mix)
LED manufacturer:	OSRAM
Color temperature:	2800K - 10000K adjustable
Max. TILT movement:	210° Exact positioning (16 bit resolution) Auto position correction (feedback)
Max. PAN movement:	540° Exact positioning (16 bit resolution) Auto position correction (feedback)
Flash rate:	1 - 16 Hz
Equipment:	Zoom motor-driven
DMX channels:	18; 25; 37; 26; 33; 45; 46; 53; 65
DMX input:	3-pin XLR (M) mounting version 5-pin XLR (M) mounting version

DMX output:	3-pin XLR (F) mounting version 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; Master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by LumenRadio upgradeable; RDM; Sound to light via Microphone
Preprogrammed in:	Light Captain
Projection:	Flicker-free
Beam angle:	1° - 48°
Beam angle (1/2 peak):	1 - 32°
Beam angle (1/10 peak):	5 - 48°
Illuminance in Lux (lx):	Narrow red (R) 3m: 6818 lx, 6m: 1758 lx Narrow green (G) 3m: 12807 lx, 6m: 3122 lx Narrow blue (B) 3m: 2513 lx, 6m: 21580 lx Narrow cold white (CW) 3m: 21580 lx, 6m: 5431 lx Narrow all 3m: 38576 lx, 6m: 9662 lx Wide red (R) 3m: 162 lx, 6m: 46 lx Wide green (G) 3m: 315 lx, 6m: 89 lx Wide blue (B) 3m: 85 lx, 6m: 25 lx Wide cold white (CW) 3m: 504 lx, 6m: 143 lx Wide all 3m: 915 lx, 6m: 259 lx
Housing color:	Black
Attachment system:	Omega bracket
Display type:	Multicolor LCD display battery buffering upgradeable
Transport aid:	Rubber feet
Dimensions:	Width: 28,6 cm Depth: 24,5 cm Height: 37,2 cm
Weight:	8,10 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)

#### **ROADINGER Flightcase 4x EYE-740 MK2 with wheels**

Maximum load:	100 kg
Aluminum profile frames:	30 mm
Case handle:	4 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Material:	Plywood multi-layer glued, 7 mm
Color:	Black, laminated
Inside dimensions:	81 cm x 53,5 cm x 36,5 cm
Device compartment:	28 cm x 17,5 cm x 36,5 cm
Accessory compartment:	10,5 cm x 53,5 cm x 36 cm

Dimensions:

Width: 87 cm

Depth: 60 cm

Height: 63 cm

---

Weight:

39,35 kg

---