



### Features:

#### EUROLITE LED Silent Bar 16x4W RGB/WW

Compact and whisper-quiet spotlight for colored and white light

- Additional frost filter provides a wide, soft and homogeneous light
- 16 LEDs 4 W SMD 3535 4in1 QCL RGB/WW<BR> segments controlled separately
- Color blend stepless; color change automatic; color fade automatic; Dimmer electronic; program speed adjustable
- Wash effect; strobe effect
- 41 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; sound to light via microphone; master/slave function; IR remote control (not included); DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for Colorchief; Light´J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
- Flicker-free
- With a beam angle of 20°
- Good color rendering index (CRI)
- With double bracket
- Monochrome 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Video and photography; clubs/dancing school; stage; wedding/gala/events; mobile djs / entertainer; party room; theater; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Standing; suspended; on stand

### Logistic

EAN / GTIN: 4026397708776

Weight: 6,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

**EUROLITE SB-15 Soft Bag**

Universal softbag

- High-quality workmanship with nylon , black
- Interior with foam padding
- 2 carrying straps

**Technical specifications:**

|         |         |
|---------|---------|
| Weight: | 5.73 kg |
|---------|---------|

**EUROLITE LED Silent Bar 16x4W RGB/WW**

|                              |                                                                                                                                                                                                                                          |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:                | 100-240 V AC, 50/60 Hz                                                                                                                                                                                                                   |
| Power consumption:           | 70 W                                                                                                                                                                                                                                     |
| IP classification:           | IP20                                                                                                                                                                                                                                     |
| Protection class:            | Protection class I                                                                                                                                                                                                                       |
| Power connection:            | Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug (provided)                                                                                                                                          |
| Power output:                | P-Con (gray), mounting version                                                                                                                                                                                                           |
| Fuse:                        | 5 x 20 mm, T 1.6 A fuse replaceable                                                                                                                                                                                                      |
| Battery:                     | 1 x button cell 3.0 V CR2032 lithium manganese<br>built-in                                                                                                                                                                               |
| Lamp type:                   | LED lamp                                                                                                                                                                                                                                 |
| LED type:                    | 16 x 4 W SMD 3535 4in1 QCL RGB/WW                                                                                                                                                                                                        |
| Flash rate:                  | 1 - 25 Hz                                                                                                                                                                                                                                |
| DMX channels:                | 4; 6; 8; 16; 18; 20                                                                                                                                                                                                                      |
| DMX input:                   | 3-pin XLR (M) mounting version                                                                                                                                                                                                           |
| DMX output:                  | 3-pin XLR (F) mounting version                                                                                                                                                                                                           |
| Cooling:                     | Passive convection cooling                                                                                                                                                                                                               |
| Control:                     | Stand-alone; sound to light via microphone;<br>master/slave function; IR remote control (not<br>included); DMX; QuickDMX via USB (optional); W-<br>DMX by wireless solution via USB (optional);<br>CRMX by LumenRadio via USB (optional) |
| Fixtures available for:      | Colorchief; Light´J; Light Captain; EASY SHOW<br>1; EASY SHOW 2; EASY SHOW 3; Colorchief                                                                                                                                                 |
| Projection:                  | Flicker-free                                                                                                                                                                                                                             |
| Beam angle:                  | 20°                                                                                                                                                                                                                                      |
| Beam angle (1/2 peak):       | 20°<br>Frost filter 30°                                                                                                                                                                                                                  |
| Beam angle (1/10 peak):      | 50°<br>Frost filter 80°                                                                                                                                                                                                                  |
| Color rendering index (CRI): | 83 Ra                                                                                                                                                                                                                                    |
| Housing color:               | Black                                                                                                                                                                                                                                    |
| Attachment system:           | Double bracket                                                                                                                                                                                                                           |

|                       |                                               |
|-----------------------|-----------------------------------------------|
| Display type:         | Monochrome 4 digit 7-segment LED display      |
| Dimensions:           | Length: 33 cm<br>Width: 17 cm<br>Depth: 17 cm |
| Weight:               | 2.73 kg                                       |
| Noise classification: | Class 0 (no noise at all)                     |
| Special product:      | Not designed for household room illumination  |
| Intended use:         | Show effect lighting                          |

#### **EUROLITE SB-15 Soft Bag**

|                 |                                                   |
|-----------------|---------------------------------------------------|
| Carrying strap: | 2 pc/pcs                                          |
| Material:       | Nylon                                             |
| Color:          | Black                                             |
| Dimensions:     | Width: 34.5 cm<br>Depth: 21.5 cm<br>Height: 22 cm |
| Weight:         | 0.27 kg                                           |

#### **Scope of delivery:**

##### **2 x EUROLITE LED Silent Bar 16x4W RGB/WW**

1 x device  
1 x user manual  
1 x power cord  
1 x frost filter

##### **1 x EUROLITE SB-15 Soft Bag**

1 x bag  
1 x segment