



Features:

EUROLITE LED BAR-8 SWING QCL bar

Tilttable LED light effect bar with 8 beams and strobe effect

- Vertical inclination angle adjustable
 - Dimmer electronic; color fade; color change; color blend adjustable; color selection
 - Strobe effect; uplight effect; multi beam effect
 - 5 integrated show programs
 - Direct color selection for 18 preset colors
 - The device is cooled by passive convection cooling
 - Control via stand-alone; IR remote control; DMX; QuickDMX via USB (optional); master/slave function; W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); sound to light via microphone
 - Fixtures available for Colorchief; Light Captain
 - Flicker-free
 - With mounting bracket
 - 4 digit 7-segment LED display
 - Mains input and output for power linking up to 8 units
 - For application areas such as: Clubs/dancing school; stage; mobile djs / entertainer; party room; restaurants, bars and hotels
 - Very quiet working noise
 - Application possibility: Standing; suspended
- spotlight**
- 8 LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
 LEDs controlled separately
 - With a beam angle of 1°
- strobes**
- 175 LEDs 0.2 W SMD 5050 cold white (CW)
7 segments controlled separately

Logistic

EAN / GTIN: 4026397757644

Weight: 84,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

- With a beam angle of 120°

ROADINGER Flightcase PRO 4x LED BAR-8 SWING with wheels

Trunk case with castors, PRO version

- With 2 accessory compartment
- 8 hinged, chromium plated case handles
- Branded hardware
- 2 high-quality butterfly locks with shut-off function
- 4 x castors with 2 locking brakes
- With 4 device compartment
- High-quality workmanship with plywood multi-layer glued 9.5 mm, black
- Aluminum profile frames 30mm with rounded edges
- 3 chrome tip-over locks

Technical specifications:

Weight: 83.05 kg

EUROLITE LED BAR-8 SWING QCL bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	80 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp
Max. TILT movement:	215° positioning
Flash rate:	0.35 - 20 Hz
DMX channels:	8; 12; 23; 27; 49
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control; DMX; QuickDMX via USB (optional); master/slave function; W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); sound to light via microphone
Fixtures available for:	Colorchief; Light Captain
Projection:	Flicker-free
PWM frequency:	7800 Hz
Illuminance in Lux (lx):	Cold white (CW) 1m: 8183 lx, 3m: 1527 lx, 6m: 372 lx Cold white (CW) 1m: 66 lx, 3m: 9 lx, 6m: 2 lx
Housing color:	Black
Attachment system:	Mounting bracket

Display type:	4 digit 7-segment LED display
USB port:	Type A
Material:	Plastic; metal
Dimensions:	Length: 100.0 cm Depth: 10.7 cm Height: 25.1 cm
Weight:	7.30 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Photobiological safety:	Risk Group 0
LED type:	175 x 0.2 W SMD 5050 cold white (CW)
Beam angle (1/2 peak):	120°
LED type:	8 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
Beam angle (1/2 peak):	1° multicolor
Diameter mounting holes:	3 x Ø11mm; 2 x Ø5mm
Material:	Metal, 3 mm
Color:	Black
Dimensions:	Length: 27.5 cm Width: 5.3 cm Height: 8 cm
Weight:	0.39 kg
Cable construction:	3 x 1.0 mm ² H05VV-F
Cable length:	Approx. 1.2 m
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase PRO 4x LED BAR-8 SWING with wheels

Maximum load:	50 kg
Aluminum profile frames:	30 mm
Case handle:	8 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs with shut-off function
Transport aid:	4 x castors with 2 locking brakes
Material:	Plywood multi-layer glued, 9.5 mm, laminated
Color:	Black
Device compartment:	100 cm x 11 cm x 27.5 cm
Accessory compartment:	13.5 cm x 35 cm x 10 cm
Inside dimensions:	122.5 cm x 77 cm x 27.5 cm
Dimensions:	Length: 123.7 cm Depth: 78.3 cm Height: 38.6 cm
Weight:	47.15 kg

Scope of delivery:

- 1 x light effect
- 1 x mounting bracket
- 1 x user manual
- 1 x power cord
- 1 x remote control
- 1 x battery