



Features:

EUROLITE LED RETRO 6 Spot ABL

Warm white blinder with additional colored LEDs for atmospheric lighting

- 6 LEDs 60 W COB (chip-on-board) amber (A)
 LEDs controlled separately
- 108 LEDs 0.1 W SMD 5050 3in1 R/G/B (homogenous color mix)
12 segments controlled separately
- Dimmer electronic
- Blinder effect
- 3 integrated show programs
- The device is cooled by temperature-controlled fan
- Control via DMX; stand-alone; sound to light; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 120°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- Built with SEETRONIC connector
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; theater; restaurants, bars and hotels; rental
- Very quiet working noise
- Application possibility: Standing; suspended
- Fixtures available for Light Captain

Logistic

EAN / GTIN: 4026397757248

Weight: 16,50 kg

Length: 0.00 m

Width: 0.00 m

Heigh: 0.00 m

EUROLITE RS-1 Retro Stand

Retro style lighting stand with bag, maximum load 25kg, height 92-155 cm

- The article is delivered pre-assembled
- The article is delivered with practical transport bag
- Adjustable height
- For application areas such as: Wedding/gala/events

Technical specifications:

Weight: 15.80 kg

EUROLITE LED RETRO 6 Spot ABL

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	200 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Cable construction:	3 x 1.5 mm ² H05VV-F
Power output:	P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	6 x 60 W COB (chip-on-board) amber (A) 108 x 0.1 W SMD 5050 3in1 R/G/B (homogenous color mix)
Flash rate:	0.8 - 20 Hz
DMX channels:	6; 10; 12; 16; 49
DMX input:	3-pin XLR (M) mounting version 5-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version 5-pin XLR (F) mounting version
Cooling:	2 x temperature-controlled fan
Control:	DMX; stand-alone; sound to light; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain
Projection:	Flicker-free
PWM frequency:	4000 Hz
Beam angle:	120°
Beam angle (1/2 peak):	120°
Color temperature:	1800K
Lamp life:	30000 h
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
USB port:	Type A
Use of brands:	Built with SEETRONIC connector
Material:	Metal

Dimensions:	Width: 36 cm Depth: 11 cm Height: 37.5 cm
Weight:	5.00 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE RS-1 Retro Stand

Maximum load:	25 kg
Height:	Maximum: 155 cm Minimum: 92 cm Adjustable in 12 steps
Attachment system:	Ø 12mm 6x M6 thread
Type (general stands):	Other stands
Material:	Steel (powder-coated)
Color:	Black
Transport dimensions:	97 cm x 14 cm x 14 cm
Base area:	Ø 120 cm
Mounting size min.:	67 cm x 57 cm x 92 cm
Mounting size max.:	102 cm x 88 cm x 155 cm
Weight:	9.50 kg

Scope of delivery:

1 x EUROLITE LED RETRO 6 Spot ABL

1 x spotlight
1 x power cord
1 x user manual

1 x EUROLITE RS-1 Retro Stand

1 x stand
1 x bag
1 x screw
1 x nut