

ROADINGER Amplifier rack SP-2, 20U, shock-proof

PRO flightcase for 483 mm devices (19"), shock-proof

Art. No.: 30109726

GTIN: 4026397344752



Features:

- Profile rails with 20 U mounting facility for 483 mm units (19"), e.g. PA amplifiers, power packs, additional equipment
- 2 removable covers (double-door version)
- Covers upholstered with foam (25 mm) for damping during transport
- Max. depth: behind the front panel 420 mm, max. depth in front panel 90 mm
- High-quality workmanship with 9 mm plywood multilayered glued, black laminated
- Aluminum profile frames (30 mm) with rounded edges
- Three-leg, medium-sized steel ball corners
- 4 high-quality butterfly locks
- 2 hinged, chrome case handles
- Delivery includes mounting screws
- Available in different height units (1 U = 44 mm)
- With profile rails suitable for 19" units
- With extra large installation depth
- 20 U
- For further information about this product, please refer to the Data Sheet under "Downloads"

Logistic

EAN / GTIN: 4026397344752

Weight: 46,00 kg

Length: 0.64 m

Width: 0.69 m

Height: 1.03 m

Bulky product

Technical specifications:

Maximum load:	100 kg
Material thickness:	9 mm
Front panel width:	19"
Mounting height:	Approx. 89 cm (20 U)

Mounting depth:	600 mm
Housing design:	20 U
Weight:	44.50 kg
Strength:	9 mm
Outside dimensions (W x D x H):	615 x 670 x 1030 mm
Inside dimensions:	
Mounting width:	483 mm (19")
Mounting height:	900 mm (20 U)
Mounting depth:	600 mm
Outer dimensions/corners:	64 mm

Scope of delivery:
