

EUROLITE LED PFE-60 WW/CW Profile Spot 20-50°

Profile spotlight, 60 W WW/CW LED, manual zoom, shutter blades, CRI>90

Art. No.: 40001722

GTIN: 4026397716641



List price: 546.21 €

incl. 19% VAT.

Features:

- 1 powerful LED COB (chip-on-board) 2in1 BCL CW/WW
- Variable color temperature 3200 K - 5600 K
- Zoom manual; Focus manual
- With a beam angle of 20° - 50°
- Dimmer electronic; pulse-width modulation variable
- Strobe effect
- Flicker-free
- Very high color rendering index (CRI)
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; RDM; Master/slave function
- Multicolor OLED display
- With Mounting bracket
- For application areas such as: Theater; Stage; Installation; Rental
- Preprogrammed in Light Captain
- Very quiet working noise
- Application possibility: Suspended; on stand

Package contents

- 1 x device, 1 x gobo holder, 1 x user manual

Logistic

EAN / GTIN: 4026397716641

Weight: 3,70 kg

Length: 0.42 m

Width: 0.20 m

Height: 0.23 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 60 W

IP classification: IP20

Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 0,75 mm ² H05VV-F
Cable length:	Approx. 1 m
Lamp type:	LED lamp
LED:	1 x COB (chip-on-board) 2in1 BCL CW/WW
Color temperature:	3200K - 5600K adjustable
Equipment:	Zoom manual; Focus manual
DMX channels:	2; 5
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; RDM; Master/slave function
Preprogrammed in:	Light Captain
Projection:	Flicker-free
Beam angle:	20° - 50°
Beam angle (1/2 peak):	20 - 50°
Beam angle (1/10 peak):	20 - 50°
Color rendering index (CRI):	94 Ra
Lamp life:	50000 h
Luminous flux:	4500 lm
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	Multicolor OLED display
Material:	Aluminum casting
Dimensions:	Length: 35,0 cm Width: 16,0 cm Height: 25,5 cm
Weight:	3,20 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Energy efficiency class (A - G):	F
Mounting bracket	
Diameter mounting holes:	1 x Ø12mm
Material:	Metal, 3 mm
Gobo holder	
Gobos:	Outside diameter 37mm Image diameter 25mm
Material:	Aluminum, 0,5 mm
Color:	Black
Dimensions:	Diameter: Ø 3 cm