

## EUROLITE LED PFE-60 RGBW Profile Spot 20-50°

Profile spotlight, 80 W 4in1 LED (RGBW), manual Zoom, shutter blades

Art. No.: 40001732

GTIN: 4026397715491



### Features:

- 1 LED 80 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
- Zoom manual; focus manual
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; pulse-width modulation variable
- Strobe effect
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; RDM; master/slave function
- Fixtures available for Light Captain
- Flicker-free
- With a beam angle of 20° - 50°
- Variable color temperature 1800 K - 10000 K
- Good color rendering index (CRI)
- With mounting bracket
- Multicolor OLED display
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; Trade fair and shop fitting; restaurants, bars and hotels; theater; rental
- Very quiet working noise
- Application possibility: Suspended; on stand

### Logistic

EAN / GTIN: 4026397715491

Weight: 3,71 kg

Length: 0.42 m

Width: 0.20 m

Height: 0.23 m

### Technical specifications:

|               |                        |
|---------------|------------------------|
| Power supply: | 100-240 V AC, 50/60 Hz |
|---------------|------------------------|

|                    |      |
|--------------------|------|
| Power consumption: | 60 W |
|--------------------|------|

|                    |      |
|--------------------|------|
| IP classification: | IP20 |
|--------------------|------|

|                                  |                                                                        |
|----------------------------------|------------------------------------------------------------------------|
| Protection class:                | Protection class I                                                     |
| Power connection:                | Fixed power supply cord with safety plug                               |
| Cable length:                    | Approx. 1 m                                                            |
| Fuse:                            | 5 x 20 mm, T 1 A fuse replaceable                                      |
| Lamp type:                       | LED lamp                                                               |
| LED type:                        | 1 x 80 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)      |
| Flash rate:                      | 1 - 19 Hz                                                              |
| Equipment:                       | Zoom manual; focus manual                                              |
| DMX channels:                    | 5; 6; 9                                                                |
| DMX input:                       | 3-pin XLR (M) mounting version                                         |
| DMX output:                      | 3-pin XLR (F) mounting version                                         |
| Cooling:                         | Temperature-controlled fan                                             |
| Control:                         | Stand-alone; DMX; RDM; master/slave function                           |
| Fixtures available for:          | Light Captain                                                          |
| Projection:                      | Flicker-free                                                           |
| Beam angle:                      | 20° - 50°                                                              |
| Beam angle (1/2 peak):           | 20 - 50°                                                               |
| Beam angle (1/10 peak):          | 20 - 50°                                                               |
| Color temperature:               | 1800K - 10000K adjustable                                              |
| Color rendering index (CRI):     | 82 Ra                                                                  |
| Lamp life:                       | 50000 h                                                                |
| Luminous flux:                   | 5000 lm                                                                |
| Housing color:                   | Black                                                                  |
| Attachment system:               | Mounting bracket                                                       |
| Display type:                    | Multicolor OLED display                                                |
| Dimensions:                      | Length: 35.0 cm<br>Width: 16.0 cm<br>Height: 25.5 cm                   |
| Weight:                          | 3.21 kg                                                                |
| Noise classification:            | Class 1 (very slight noise, suitable for noise-sensitive environments) |
| Energy efficiency class (A - G): | F                                                                      |
| EPREL-Nr:                        | 1597530                                                                |
| Diameter mounting holes:         | 1 x Ø12mm                                                              |
| Material:                        | Metal, 3 mm                                                            |
| Gobos:                           | Outside diameter 37mm<br>Image diameter 25mm                           |
| Material:                        | Aluminum, 0.5 mm; plastic                                              |
| Dimensions:                      | Diameter: Ø 3 cm                                                       |

## Scope of delivery:

1 x spotlight  
1 x gobo holder  
1 x user manual