


EUROLITE LED Mini PFE-12 WW

Fanless spotlight with 12 W COB LED, adjustable light beam shape, color rendering index (CRI) >90

Art. No.: 40001761













List price: 71.28 €

incl. 19% VAT.

Features:

- 4 shutter blades
- 1 powerful LED COB (chip-on-board)
- Focus manual
- Spot effect
- The device is cooled by passive convection cooling
- Easy installation
- With a beam angle of 28°
- Very high color rendering index (CRI)
- With mounting bracket
- Various versions available
- For application areas such as: Trade fair and shop fitting; installation; restaurants, bars and hotels; video and photography
- Very quiet working noise
- Application possibility: Suspended

Package contents

- 1 x spotlight, 1 x key, 1 x user manual

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	12 W
IP classification:	IP20
Protection class:	Protection class I

Logistic

EAN / GTIN: 4026397742091

Weight: 0,67 kg Length: 0.24 m Width: 0.20 m Heigth: 0.14 m

Cable construction: 3 x 0,75 mm² H05VV-F LED type: 1 x COB (chip-on-board) Equipment: Focus manual Cooling: Passive convection cooling Setup: Easy installation Beam angle: 28° Beam angle (1/2 peak): Color temperature: 2778K Color rendering index (CRI): 98 Ra Illuminance in Lux (lx): Warm white (WW) 1m: 2388 lx, 3m: 282,5 lx, 6m: 70,06 lx Luminous flux: 960 lm Housing color: Black matte Attachment system: Mounting bracket Material: Aluminum casting Dimensions: Length: 19 cm Width: 8,5 cm Height: 12,5 cm Weight: 0,50 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Energy efficiency class (A - G):	Power connection:	Fixed power supply cord with safety plug
Equipment: Focus manual Cooling: Passive convection cooling Setup: Easy installation Beam angle: 28° Beam angle (1/2 peak): Color temperature: 2778K Color rendering index (CRI): 98 Ra Illuminance in Lux (lx): Warm white (WW) 1m: 2388 lx, 3m: 282,5 lx, 6m: 70,06 lx Luminous flux: 960 lm Housing color: Black matte Attachment system: Mounting bracket Material: Aluminum casting Dimensions: Length: 19 cm Width: 8,5 cm Height: 12,5 cm Weight: 0,50 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	Cable construction:	3 x 0,75 mm² H05VV-F
Cooling: Passive convection cooling Setup: Easy installation Beam angle: 28° Beam angle (1/2 peak): 28° Color temperature: 2778K Color rendering index (CRI): 98 Ra Illuminance in Lux (lx): Warm white (WW) 1m: 2388 lx, 3m: 282,5 lx, 6m: 70,06 lx Luminous flux: 960 lm Housing color: Black matte Attachment system: Mounting bracket Material: Aluminum casting Dimensions: Length: 19 cm Width: 8,5 cm Height: 12,5 cm Weight: 0,50 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	LED type:	1 x COB (chip-on-board)
Setup: Beam angle: Beam angle (1/2 peak): Color temperature: Color rendering index (CRI): Beam with the set of the s	Equipment:	Focus manual
Beam angle: 28° Beam angle (1/2 peak): 28° Color temperature: 2778K Color rendering index (CRI): 98 Ra Illuminance in Lux (lx): Warm white (WW) 1m: 2388 lx, 3m: 282,5 lx, 6m: 70,06 lx Luminous flux: 960 lm Housing color: Black matte Attachment system: Mounting bracket Material: Aluminum casting Dimensions: Length: 19 cm Width: 8,5 cm Height: 12,5 cm Weight: 0,50 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	Cooling:	Passive convection cooling
Beam angle (1/2 peak): Color temperature: 2778K Color rendering index (CRI): 98 Ra Illuminance in Lux (lx): Warm white (WW) 1m: 2388 lx, 3m: 282,5 lx, 6m: 70,06 lx Luminous flux: 960 lm Housing color: Black matte Attachment system: Mounting bracket Material: Aluminum casting Dimensions: Length: 19 cm Width: 8,5 cm Height: 12,5 cm Weight: 0,50 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	Setup:	Easy installation
Color temperature: Color rendering index (CRI): 98 Ra Illuminance in Lux (Ix): Warm white (WW) 1m: 2388 Ix, 3m: 282,5 Ix, 6m: 70,06 Ix Luminous flux: 960 Im Housing color: Black matte Attachment system: Mounting bracket Material: Aluminum casting Dimensions: Length: 19 cm Width: 8,5 cm Height: 12,5 cm Weight: 0,50 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	Beam angle:	28°
Color rendering index (CRI): 98 Ra Illuminance in Lux (lx): Warm white (WW) 1m: 2388 lx, 3m: 282,5 lx, 6m: 70,06 lx Luminous flux: 960 lm Housing color: Black matte Attachment system: Mounting bracket Aluminum casting Dimensions: Length: 19 cm Width: 8,5 cm Height: 12,5 cm Weight: 0,50 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	Beam angle (1/2 peak):	28°
Illuminance in Lux (lx): Warm white (WW) 1m: 2388 lx, 3m: 282,5 lx, 6m: 70,06 lx Luminous flux: 960 lm Housing color: Black matte Attachment system: Mounting bracket Aluminum casting Dimensions: Length: 19 cm Width: 8,5 cm Height: 12,5 cm Weight: 0,50 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	Color temperature:	2778K
To,06 lx Luminous flux: 960 lm Housing color: Attachment system: Mounting bracket Material: Aluminum casting Dimensions: Length: 19 cm Width: 8,5 cm Height: 12,5 cm Weight: 0,50 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	Color rendering index (CRI):	98 Ra
Housing color: Attachment system: Mounting bracket Material: Aluminum casting Dimensions: Length: 19 cm Width: 8,5 cm Height: 12,5 cm Weight: 0,50 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	Illuminance in Lux (lx):	Warm white (WW) 1m: 2388 lx, 3m: 282,5 lx, 6m: 70,06 lx
Attachment system: Mounting bracket Aluminum casting Dimensions: Length: 19 cm Width: 8,5 cm Height: 12,5 cm Weight: 0,50 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	Luminous flux:	960 lm
Material: Aluminum casting Length: 19 cm Width: 8,5 cm Height: 12,5 cm Weight: 0,50 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	Housing color:	Black matte
Dimensions: Length: 19 cm Width: 8,5 cm Height: 12,5 cm Weight: 0,50 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	Attachment system:	Mounting bracket
Width: 8,5 cm Height: 12,5 cm Weight: 0,50 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	Material:	Aluminum casting
Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	Dimensions:	Width: 8,5 cm
sensitive environments)	Weight:	0,50 kg
Energy efficiency class (A - G):	Noise classification:	
	Energy efficiency class (A - G):	F