

EUROLITE LED PFE-20 WW Profile Spot bk

Handy stage spotlight with 20 W COB LED, CRI >95

Art. No.: 40001766

GTIN: 4026397693072



List price: 213.01 €

incl. 19% VAT.

Features:

- 4 shutter blades
 - 1 powerful LED 20 W COB (chip-on-board) warm white (WW)
 - Dimmer electronic
 - The device is cooled by passive convection cooling
 - Flicker-free
 - With a beam angle of 19°
 - Very high color rendering index (CRI)
 - With mounting bracket
 - For application areas such as: Trade fair and shop fitting; installation; restaurants, bars and hotels; video and photography
 - Silent operation
 - Application possibility: Suspended; on stand
- screw**
- M5 thread
- Package contents**
- 1 x spotlight, 1 x gobo holder, 1 x filter frame, 2 x screw, 2 x washer, 1 x user manual

Logistic

EAN / GTIN: 4026397693072

Weight: 1,40 kg

Length: 0.25 m

Width: 0.13 m

Height: 0.15 m

Technical specifications:

| | |
|--------------------|------------------------|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 20 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |

| | |
|------------------------------|---|
| Power connection: | Mains input via 3-pin screw plug connector (M) mounting version power supply cord with safety plug (provided) |
| Fuse: | 5 x 20 mm, T 0,5 A fuse replaceable |
| Lamp type: | LED lamp |
| LED type: | 1 x 20 W COB (chip-on-board) warm white (WW) |
| Cooling: | Passive convection cooling |
| Projection: | Flicker-free |
| Beam angle: | 19° |
| Beam angle (1/2 peak): | 19° |
| Color temperature: | 3000K |
| Color rendering index (CRI): | 97 Ra |
| Illuminance in Lux (lx): | Warm white (WW) 1m: 5177 lx, 3m: 611 lx, 6m: 154 lx |
| Housing color: | Black matte |
| Attachment system: | Mounting bracket |
| Material: | Aluminum casting; metal; plastic |
| Dimensions: | Length: 22,2 cm Width: 15,8 cm Height: 20,3 cm |
| Weight: | 1,23 kg |
| Noise classification: | Class 0 (no noise at all) |
| Gobo holder | |
| Gobos: | Outside diameter 42mm Image diameter 18mm |
| Material: | Aluminum, 0,3 mm |
| Dimensions: | Width: 4,4 cm Height: 10,1 cm Diameter: Ø 3,4 cm |
| Power cord | |
| Cable construction: | 3 x 0,75 mm² H05VV-F |
| Cable length: | Approx. 1,4 m |
| Filter frame | |
| Material: | Aluminum, 0,3 mm |
| Dimensions: | Width: 6,9 cm Height: 6,9 cm Diameter: Ø 5,6 cm |
| Mounting bracket | |
| Diameter mounting holes: | 1 x Ø11mm; 2 x Ø7mm |
| Material: | Aluminum casting, 2 mm |
| Screw | |
| Thread: | M5 thread x 11 mm |
| Washer | |
| Material: | Plastic |
| Color: | Pink |
| Dimensions: | Height: 0,1 cm Diameter: Ø 1,2 cm |

| | |
|----------------------|--|
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |