

EUROLITE LED PLL-704 6000K Panel

DMX-controlled surface light with 704 cold white LEDs, QuickDMX port and barn doors

Art. No.: 40001835

GTIN: 4026397700244



List price: 593.81 €

incl. 19% VAT.

Features:

- 704 powerful LEDs SMD 2835 cold white (CW)
- Energy-saving, durable and environmentally friendly
- 4 barn doors to avoid blinding the audience and for protection during transport
- Pulse-width modulation variable
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; Quick select potentiometer for brightness and flash rate; Master/slave function; Sound to light via Microphone; W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional)
- Flicker-free
- With a beam angle of 120°
- Good color rendering index (CRI)
- With Mounting bracket
- LCD display
- Slim, rugged metal housing
- For application areas such as: Video and photography; Stage; Trade fair and shop fitting; mobile use
- Preprogrammed in Light Captain; Light J
- Mains input and output for power linking up to 8 units
- Rugged carrying handle
- Silent operation
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x power cord, 1 x user manual

Logistic

EAN / GTIN: 4026397700244

Weight: 8,50 kg

Length: 0.57 m

Width: 0.18 m

Height: 0.40 m

Technical specifications:

| | |
|------------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 140 W |
| IP classification: | IP20 |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | P-Con (gray), mounting version |
| Fuse: | T 3 A Fuse replaceable |
| Lamp type: | LED lamp |
| LED: | 704 x SMD 2835 cold white (CW) |
| Color temperature: | 6000K |
| Flash rate: | 0 - 20 Hz |
| DMX channels: | 1; 2; 3 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; DMX; Quick select potentiometer for brightness and flash rate; Master/slave function; Sound to light via Microphone; W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional) |
| Preprogrammed in: | Light Captain; Light J |
| Projection: | Flicker-free |
| Beam angle: | 120° |
| Beam angle (1/2 peak): | 120° |
| Color rendering index (CRI): | 80 Ra |
| Illuminance in Lux (lx): | Cold white (CW) 1m: 4111 lx, 3m: 598 lx, 6m: 182 lx |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Display type: | LCD display |
| Carrying handle: | 1 pc/pcs |
| Dimensions: | Width: 56,5 cm Depth: 25,5 cm Height: 42,2 cm |
| Weight: | 7,70 kg |
| Noise classification: | Class 0 (no noise at all) |
| Photobiological safety: | Risk Group 0 |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |