

EUROLITE LED KKL-12 Floodlight 3200K black

Warm white 12 W LED light on an extension arm with clamp holder

Art. No.: 41600462

GTIN: 4026397606652



Description:

The Eurolite KKL-12 LED floodlight illuminates trade fair booths, shop windows, workshops and even weatherproof outdoor areas.

You can purchase the KKL-12 in three simple casing colors: black, white and silver.

Features:

- Inclination angle of the LED head manually adjustable
- Unique design
- 12 LEDs 1 W high-power warm white (WW)
- The device is cooled by passive convection cooling
- Control via plug and play
- Easy installation
- With a beam angle of 40°
- Various versions available
- For application areas such as: Decoration; Trade fair and shop fitting; advertisement/Shop window
- Silent operation
- Application possibility: Suspended; wall mounting

Logistic

EAN / GTIN: 4026397606652

Weight: 0,96 kg

Length: 0.49 m

Width: 0.14 m

Height: 0.06 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 12 W

IP classification:	IP20
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 0.75 mm ² H05VV-F
Cable length:	Approx. 1.5 m
Lamp type:	LED lamp
LED type:	12 x 1 W high-power warm white (WW)
Inclination angle:	Horizontal: 320 °; vertical: 85 °
Cooling:	Passive convection cooling
Control:	Plug and play
Setup:	Easy installation
Beam angle:	40°
Beam angle (1/2 peak):	40°
Beam angle (1/10 peak):	75°
Color temperature:	3200K
Illuminance in Lux (lx):	1m: 1028 lx, 3m: 134 lx, 6m: 38 lx
Luminous flux:	752 lm
Housing color:	Black
Dimensions:	Length: 45 cm Width: 13 cm Depth: 12 cm
Weight:	0.81 kg
Noise classification:	Class 0 (no noise at all); Class 0 (no noise at all)
Energy efficiency class (A - G):	G
EPREL-Nr:	1263088

Scope of delivery:

- 1 x spotlight
- 1 x knurled screw
- 1 x plate
- 1 x user manual