

## EUROLITE LED Theatre COB 100 RGB+WW

LED theatre spot with 4in1 QCL RGB/WW 100 W COB (chip-on-board) LED

Art. No.: 41602018

GTIN: 4026397685909



**List price: 248.71 €**

incl. 19% VAT.

### Features:

- 1 powerful LED 100 W COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix)
  - Strobe effect
  - Integrated show programs
  - The device is cooled by cooling fan
  - Control via stand-alone; DMX; Master/slave function; Sound to light via Microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
  - Flicker-free
  - With a beam angle of 41°
  - Very high color rendering index (CRI)
  - With double bracket
  - 4 digit 7-segment LED display
  - For application areas such as: Concerts/FoH's; Clubs/dancing school; Stage; small rental
  - Dimmer electronic
  - Preprogrammed in LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J; Light Captain; EASY SHOW 2; EASY SHOW 3
  - Mains input and output for power linking up to 8 units
  - Application possibility: Standing; suspended; on stand
- Package contents**
- 1 x spotlight, 1 x power cord, 1 x barn door, 1 x user manual

### Logistic

EAN / GTIN: 4026397685909

Weight: 3,10 kg

Length: 0.26 m

Width: 0.23 m

Height: 0.34 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	70 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Fuse:	T 1 A Fuse replaceable
Lamp type:	LED lamp
LED:	1 x 100 W COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix)
DMX channels:	4; 5; 6; 9
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	1 x cooling fan
Control:	Stand-alone; DMX; Master/slave function; Sound to light via Microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	41°
Beam angle (1/2 peak):	41°
Beam angle (1/10 peak):	65°
Color rendering index (CRI):	92 Ra
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 25,0 cm Depth: 32,0 cm Height: 29,0 cm
Weight:	2,75 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Photobiological safety:	Risk Group 0
Power cord	
Cable construction:	3 x 1,0 mm <sup>2</sup> H05VV-F
Cable length:	Approx. 1,1 m
Mounting bracket	
Diameter mounting holes:	1 x Ø11mm
Material:	Metal, 2,5 mm
Barndoor	
Material:	Metal, 0,8 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting