

EUROLITE LED Theatre COB 100 RGB+WW

LED theatre spot with 4in1 QCL RGB/WW 100 W COB (chip-on-board) LED

Art. No.: 41602018

GTIN: 4026397685909



Features:

- 1 LED 100 W COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix)
- Dimmer electronic
- Strobe effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 41°
- Very high color rendering index (CRI)
- With double bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; decoration; wedding/gala/events; restaurants, bars and hotels; video and photography; advertisement/Shop window
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397685909

Weight: 3,20 kg

Length: 0.26 m

Width: 0.23 m

Height: 0.34 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 70 W

IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Fuse:	T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 100 W COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix)
Flash rate:	0.5 - 24 Hz
DMX channels:	4; 5; 6; 9
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	1 x cooling fan
Control:	Stand-alone; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle:	41°
Beam angle (1/2 peak):	41°
Beam angle (1/10 peak):	65°
Color rendering index (CRI):	92 Ra
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 25.0 cm Depth: 32.0 cm Height: 29.0 cm
Weight:	2.85 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Photobiological safety:	Risk Group 0
Cable construction:	3 x 1.0 mm ² H05VV-F
Cable length:	Approx. 1.1 m
Material:	Metal, 0.8 mm
Diameter mounting holes:	1 x Ø11mm
Material:	Metal, 2.5 mm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x spotlight
1 x power cord
1 x user manual