

## EUROLITE LED Theatre COB 100 UV

LED theatre spot with ultra violet (UV) 100 W COB (chip-on-board) LED

Art. No.: 41602020

GTIN: 4026397702378



**List price: 296.31 €**

incl. 19% VAT.

### Features:

- 1 powerful LED 100 W COB (chip-on-board) ultra violet (UV)
- UV effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; Sound to light via Microphone; Master/slave function; CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional)
- Flicker-free
- With a beam angle of 40°
- 4 digit 7-segment LED display
- Dimmer electronic
- Preprogrammed in Light´J; Light Captain
- Mains input and output for power linking up to 8 units
- With bracket for floor use
- For application areas such as: Clubs/dancing school; Stage; theater; mobile djs / entertainer
- Application possibility: Standing; suspended; on stand

#### Package contents

- 1 x spotlight, 1 x power cord, 1 x user manual

### Logistic

EAN / GTIN: 4026397702378

Weight: 3,10 kg

Length: 0.26 m

Width: 0.23 m

Height: 0.34 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 85 W

IP classification: IP20

Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 1 A Fuse replaceable
Lamp type:	LED lamp
LED:	1 x 100 W COB (chip-on-board) ultra violet (UV)
Flash rate:	0 - 20 Hz
DMX channels:	1; 4
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; Sound to light via Microphone; Master/slave function; CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional)
Preprogrammed in:	Light´J; Light Captain
Projection:	Flicker-free
Beam angle:	40°
Beam angle (1/2 peak):	40°
Beam angle (1/10 peak):	70°
Illuminance in Lux (lx):	Ultra violet (UV) 1m: 38 lx, 3m: 6 lx, 6m: 2 lx
Wavelength:	Ultra violet (UV) 402 nm
Housing color:	Black
Attachment system:	Bracket for floor use
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 24,3 cm Depth: 31,1 cm Height: 32,0 cm
Weight:	2,75 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting