

EUROLITE LED Theatre COB 200 RGB+WW

LED theatre spot with 4in1 QCL RGB/WW W COB (chip-on-board) LED

Art. No.: 41602038

GTIN: 4026397686531



List price: 427.21 €

incl. 19% VAT.

Features:

- 1 powerful LED COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix)
- Variable color temperature 1800 K - 8000 K
- Dimmer electronic
- Strobe effect
- 9 integrated show programs
- Direct color selection for 27 preset colors
- The device is cooled by cooling fan
- Control via stand-alone; IR remote control; DMX; Master/slave function; Sound to light via Microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 17°
- Very high color rendering index (CRI)
- With double bracket
- LCD display
- Silent operation
- For application areas such as: Theater; concerts/FoH's; Clubs/dancing school; Stage
- Preprogrammed in Light´J; Light Captain; EASY SHOW 2; EASY SHOW 3
- Mains input and output for power linking up to 8 units
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

Logistic

EAN / GTIN: 4026397686531

Weight: 4,96 kg

Length: 0.45 m

Width: 0.31 m

Height: 0.28 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	140 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Lamp type:	LED lamp
LED:	1 x COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix)
Color temperature:	1800K - 8000K adjustable
Flash rate:	0 - 20 Hz
DMX channels:	3; 4; 5; 6; 10
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; IR remote control; DMX; Master/slave function; Sound to light via Microphone; QuickDMX via USB (optional); W- DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light´J; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	17°
Beam angle (1/2 peak):	17°
Beam angle (1/10 peak):	35°
Color rendering index (CRI):	95 Ra
Housing color:	Black
Attachment system:	Double bracket
Display type:	LCD display
Material:	Aluminum casting; metal
Dimensions:	Width: 25,95 cm Depth: 20,00 cm Height: 37,65 cm
Weight:	4,11 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Power cord	
Cable construction:	3 x 1,0 mm² H05RN-F
Cable length:	Approx. 1,2 m
Mounting bracket	
Diameter mounting holes:	3 x Ø11mm
Material:	Metal, 3 mm

Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting