

EUROLITE LED Theatre COB 200 RGB+WW

LED theatre spot with 4in1 QCL RGB/WW W COB (chip-on-board) LED

Art. No.: 41602038

GTIN: 4026397686531



Features:

- 1 LED COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix)
- Dimmer electronic
- Strobe effect
- 9 integrated show programs
- Direct color selection for 27 preset colors
- The device is cooled by cooling fan
- Control via stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for Light'J; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 17°
- Variable color temperature 1800 K - 8000 K
- Very high color rendering index (CRI)
- With double bracket
- LCD display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; restaurants, bars and hotels; theater; rental; video and photography
- Very quiet working noise
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397686531

Weight: 4,96 kg

Length: 0.45 m

Width: 0.31 m

Height: 0.28 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	140 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	1 x COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix)
Flash rate:	0.5 - 24 Hz
DMX channels:	3; 4; 5; 6; 10
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light'J; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
PWM frequency:	2900 Hz
Beam angle (1/2 peak):	17°
Beam angle (1/10 peak):	35°
Color temperature:	1800K - 8000K adjustable
Color rendering index (CRI):	95 Ra
Housing color:	Black
Attachment system:	Double bracket
Display type:	LCD display
Material:	Aluminum casting; metal
Dimensions:	Width: 25.95 cm Depth: 20.00 cm Height: 37.65 cm
Weight:	4.11 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Photobiological safety:	Risk Group 0
Cable construction:	3 x 1.0 mm ² H05RN-F
Cable length:	Approx. 1.2 m
Diameter mounting holes:	3 x Ø11mm
Material:	Metal, 3 mm

Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

- 1 x spotlight
- 1 x power cord
- 1 x remote control
- 1 x battery
- 1 x user manual