

## EUROLITE LED THA-120PC Theater Spot

Art. No.: 41602130

Fresnel spotlight (fresnel lens), 120-W-COB (chip-on-board)-LED 4in1 QCL RGBW, extremely quiet, DMX GTIN: 4026397578447



### Features:

- Compact design
- 1 LED 120 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
- Dimmer electronic; color change adjustable; color fade adjustable; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; sound to light via microphone
- Fixtures available for LED PC-Control 512; Light' J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
- Flicker-free
- With a beam angle of 3° - 43°
- With mounting bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; wedding/gala/events; restaurants, bars and hotels; theater; rental; video and photography
- Application possibility: Suspended; on stand

### Logistic

EAN / GTIN: 4026397578447

Weight: 6,60 kg

Length: 0.49 m

Width: 0.32 m

Height: 0.32 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 135 W

IP classification: IP20

|                         |   |
|-------------------------|---|
| Power connection:       | Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)   |
| Power output:           | 1 x PowerCON (gray), mounting version   |
| Lamp type:              | LED lamp  |
| LED type:               | 1 x 120 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)  |
| DMX channels:           | 4; 6; 7   |
| DMX input:              | 1 x 3-pin XLR (M) mounting version<br>1 x 5-pin XLR (M) mounting version  |
| DMX output:             | 1 x 3-pin XLR (F) mounting version<br>1 x 5-pin XLR (F) mounting version  |
| Cooling:                | Temperature-controlled fan  |
| Control:                | Stand-alone; DMX; sound to light via microphone   |
| Fixtures available for: | LED PC-Control 512; Light J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3 |
| Projection:             | Flicker-free  |
| Beam angle:             | 3° - 43°  |
| Beam angle (1/2 peak):  | 3 - 32°   |
| Beam angle (1/10 peak): | 9 - 43°   |
| Housing color:          | Black   |
| Attachment system:      | Mounting bracket  |
| Dimensions:             | Length: 37 cm<br>Width: 25.6 cm<br>Depth: 36 cm   |
| Weight:                 | 5.85 kg   |
| Noise classification:   | Class 2 (slight noise)  |
| Special product:        | Not designed for household room illumination  |
| Intended use:           | Show effect lighting  |

### Scope of delivery:

1 x spotlight  
1 x user manual  
1 x power cord  
1 x filter frame