

EUROLITE LED THA-250F P.O. Theater-Spot

Pole operated fresnel spotlight (fresnel lens), warm white 200 W LED, CRI >90, quiet, DMX

Art. No.: 41602138

GTIN: 4026397735505



Features:

- Pole-operated bracket for pan & tilt control
- 1 LED 200 W COB (chip-on-board) warm white (WW)
- Zoom motor driven
- Dimmer electronic; dimmer curves with adjustable response; Dimmer speed (step response) adjustable
- Wash effect; strobe effect
- The device is cooled by temperature-controlled fan
- Control via quick select potentiometer for brightness and Zoom; DMX; RDM
- Flicker-free
- RDM For bidirectional communication over the DMX line
- DMX fail mode (hold; blackout)
- With a beam angle of 5° - 28°
- Very high color rendering index (CRI)
- TV spigot
- Monochrome LCD display
- Rubber feet
- Mains input and output for power linking up to 8 units
- Built with NEUTRIK connector
- For application areas such as: Theater; stage; wedding/gala/events; Trade fair and shop fitting; video and photography
- Very quiet working noise
- Application possibility: Suspended

Logistic

EAN / GTIN: 4026397735505

Weight: 15,50 kg

Length: 0.81 m

Width: 0.41 m

Height: 0.42 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	240 W
IP classification:	IP20
Protection class:	Protection class I
Power output:	PowerCON (gray), mounting version
Fuse:	5 x 20 mm, T 3 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 200 W COB (chip-on-board) warm white (WW)
Flash rate:	1.5 - 12 Hz
Equipment:	Zoom motor driven
Color generation:	Via color filter frame
DMX channels:	3
DMX input:	3-pin XLR (M) mounting version 5-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Quick select potentiometer for brightness and Zoom; DMX; RDM
Projection:	Flicker-free
PWM frequency:	3600 Hz
DMX features:	RDM For bidirectional communication over the DMX line
DMX fail mode:	Hold; blackout
Beam angle:	5° - 28°
Beam angle (1/2 peak):	5 - 28°
Beam angle (1/10 peak):	12 - 28°
Color temperature:	2800K
Color rendering index (CRI):	91 Ra
Housing color:	Black
Attachment system:	TV spigot Ø 28mm
Display type:	Monochrome LCD display
Transport aid:	Rubber feet
Use of brands:	Built with NEUTRIK connector
Material:	Metal
Dimensions:	Length: 45.5 cm Width: 33.5 cm Height: 61.5 cm
Weight:	11.90 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Special product:	Not designed for household room illumination

Intended use:

Show effect lighting

Scope of delivery:

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 1 x filter frame
- 1 x barndoor