

## EUROLITE LED THA-500F Theater Spot

Art. No.: 41602180

Fresnel spotlight (fresnel lens), 450-W-COB (chip-on-board)-LED warm white (WW), extremely quiet, DMX, GTIN: 4026397731569



### Features:

- Rugged metal housing
- Rubber-coated handle
- 1 LED 450 W COB (chip-on-board) warm white (WW)
- Zoom motor driven; zoom manual
- Dimmer curves with adjustable response; Dimmer electronic; pulse-width modulation variable; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; RDM; rotary dial for brightness; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
- Flicker-free
- With a beam angle of 8° - 56°
- Very high color rendering index (CRI)
- With mounting bracket
- Monochrome LCD display
- 4 x rubber feet
- Mains input and output for power linking up to 4 units
- Built with SEETRONIC connector
- For application areas such as: Stage; wedding/gala/events; Trade fair and shop fitting; theater; rental; video and photography
- Very quiet working noise
- Application possibility: Standing; suspended

### Logistic

EAN / GTIN: 4026397731569

Weight: 13,30 kg

Length: 0.59 m

Width: 0.41 m

Height: 0.41 m

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	475 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 6.3 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 450 W COB (chip-on-board) warm white (WW)
Equipment:	Zoom motor driven; zoom manual
DMX channels:	1; 2; 4; 8
DMX input:	3-pin XLR (M) mounting version 5-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; RDM; rotary dial for brightness; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
Projection:	Flicker-free
Beam angle:	8° - 56°
Beam angle (1/2 peak):	8 - 43°
Beam angle (1/10 peak):	15 - 56°
Color temperature:	3000K
Color rendering index (CRI):	96 Ra
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	Monochrome LCD display
Transport aid:	4 x rubber feet
Use of brands:	Built with SEETRONIC connector
Dimensions:	Length: 44.0 cm Width: 34.0 cm Height: 43.5 cm
Weight:	10.45 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

## Scope of delivery:

---

- 1 x spotlight
- 1 x power cord
- 1 x user manual
- 1 x barndoor