

## EUROLITE LED PAR-64 COB 3000K 100W Zoom bk

PAR spot with warm white 100 W COB LED and manual zoom

Art. No.: 41603600

GTIN: 4026397645156



**List price: 355.81 €**

incl. 19% VAT.

### Features:

- Light performance comparable to a traditional 1000 W halogen spot light
- Homogeneous light distribution
- 1 powerful LED 100 W COB (chip-on-board) warm white (WW)
- Strobe effect
- The device is cooled by cooling fan
- Control via DMX
- Flicker-free
- With a beam angle of 11° - 48°
- Very high color rendering index (CRI)
- With Mounting bracket
- 4 digit 7-segment LED display
- For application areas such as: Theater; Trade fair and shop fitting; Stage; Rental
- Dimmer speed (step response) adjustable; Gamma correction adjustable; pulse-width modulation variable
- Preprogrammed in Light´J; Light Captain
- Mains input and output for power linking up to 8 units
- Application possibility: Suspended; on stand

#### Package contents

- 1 x spotlight, 1 x power cord, 1 x filter frame, 1 x xLR cable, 1 x mounting bracket, 2 x knurled screw, 2 x washer, 1 x user manual

### Logistic

EAN / GTIN: 4026397645156

Weight: 4,70 kg

Length: 0.50 m

Width: 0.38 m

Height: 0.38 m

### Technical specifications:

Power supply:

100-240 V AC, 50/60 Hz

Power consumption:	110 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Lamp type:	LED lamp
LED:	1 x 100 W COB (chip-on-board) warm white (WW)
Color temperature:	3000K
Flash rate:	0 - 25 Hz
DMX channels:	1; 2; 3
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX
Preprogrammed in:	Light'J; Light Captain
Projection:	Flicker-free
Beam angle:	11° - 48°
Beam angle (1/2 peak):	11 - 35°
Beam angle (1/10 peak):	15 - 48°
Color rendering index (CRI):	91 Ra
Illuminance in Lux (lx):	Narrow warm white (WW) 3m: 15535 lx, 6m: 3666 lx Wide warm white (WW) 3m: 2387 lx, 6m: 654 lx
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Material:	Aluminum; metal
Dimensions:	Width: 26 cm Depth: 43,5 cm Height: 37,5 cm
Weight:	3,55 kg
Noise classification:	Class 2 (slight noise)
Power cord	
Cable construction:	3 x 1,0 mm <sup>2</sup> H05VV-F
Cable length:	Approx. 1,5 m
XLR cable	
Cable length:	Approx. 1,8 m
Color:	Black
Mounting bracket	
Diameter mounting holes:	1 x Ø10mm; 2 x Ø8mm
Material:	Aluminum, 4 mm
Filter frame	
Shape:	Octagonal
Material:	Aluminum, 0,5 mm

Dimensions:

Width: 24,8 cm

Height: 24,8 cm

Diameter: Ø 19,8 cm

---