

EUROLITE LED IP PAR-64 COB 3000K 100W Zoom bk

Weather-proof PAR spot, IP65, with warm white 100 W COB LED and motorized zoom

Art. No.: 41603610

GTIN: 4026397698152



Features:

- Light performance comparable to a traditional 1000 W halogen spot light
- Homogeneous light distribution
- 1 LED 100 W COB (chip-on-board) warm white (WW)
- Zoom motor driven
- Dimmer curves with adjustable response; pulse-width modulation variable; Gamma correction adjustable; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by temperature-controlled fan
- Control via DMX; stand-alone; master/slave function
- Fixtures available for Light Captain
- Flicker-free
- With a beam angle of 7° - 53°
- Very high color rendering index (CRI)
- With double bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- For application areas such as: Architecture; stage; wedding/gala/events; Trade fair and shop fitting; theater; rental; video and photography
- Application possibility: Suspended; on stand

Logistic

EAN / GTIN: 4026397698152

Weight: 9,15 kg

Length: 0.48 m

Width: 0.30 m

Height: 0.29 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	120 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Power output:	IP T-Con (F) mounting version
Fuse:	T 6.3 A fuse fix in power supply
Lamp type:	LED lamp
LED type:	1 x 100 W COB (chip-on-board) warm white (WW)
Flash rate:	0 - 20 Hz
Equipment:	Zoom motor driven
DMX channels:	1; 2; 3; 4
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Temperature-controlled fan
Control:	DMX; stand-alone; master/slave function
Fixtures available for:	Light Captain
Projection:	Flicker-free
Beam angle:	7° - 53°
Beam angle (1/2 peak):	7 - 36°
Beam angle (1/10 peak):	9 - 53°
Color temperature:	3000K
Color rendering index (CRI):	90 Ra
Housing color:	Black matte
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Material:	Aluminum casting
Dimensions:	Length: 36 cm Width: 29 cm Height: 35 cm
Weight:	8.40 kg
Noise classification:	Class 2 (slight noise)
Cable construction:	3 x 1.5 mm² H07RN-F
Cable length:	Approx. 1.5 m
Cable length:	Approx. 1 m
Connector type:	3-pin XLR (M); 3-pin XLR (F)
Diameter mounting holes:	1 x Ø10mm
Material:	Metal, 2.5 mm

Scope of delivery:

1 x device
 1 x power cord
 1 x XLR cable
 2 x mounting bracket
 2 x knurled screw
 4 x washer
 1 x user manual