

EUROLITE SUNSET IP EYE 1 Blinder dim2warm

Weather-proof (IP65) blinder with 324W LED and excellent tungsten simulation

Art. No.: 41604105

GTIN: 4026397755534



Description:

Who does not remember the classic halogen blinders, especially their warm, golden glow when dimmed down? This weatherproof LED blinder recreates that exact behavior with impressive accuracy.

As it is dimmed, the light gradually shifts into the characteristic golden tone. Even at low brightness levels, this warm color is maintained, creating a distinctive atmosphere.

The high-output LED delivers enough brightness to produce strong blinder effects even on large outdoor stages, while also providing that signature warm look when dimmed.

Features:

- 1 LED 324 W COB (chip-on-board) Dim to warm (homogenous color mix)
- Dimmer electronic; dimmer curves adjustable; Dimmer speed (step response) adjustable; pulse-width modulation adjustable; Dim to warm
- Blinder effect; strobe effect
- 3 integrated show programs
- Control via DMX; RDM; stand-alone; master/slave function
- RDM For bidirectional communication over the DMX line
- DMX fail mode (hold; blackout)
- With a beam angle of 73°
- Good color rendering index (CRI)
- Flicker-free
- With omega bracket
- Multicolor LCD display
- The device is cooled by temperature-controlled fan

Logistic

EAN / GTIN: 4026397755534

Weight: 6,30 kg

Length: 0.39 m

Width: 0.35 m

Height: 0.25 m

- Mains input and output for power linking up to 8 units
- Built with SEETRONIC connector
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; rental; theater
- Application possibility: Standing; suspended; on stand
- Silent operation
- Fixtures available for Light´J; Light Captain
screw
- With mounting bracket

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	180 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Cable construction:	3 x 2.5 mm ² H07RN-F
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	1 x 324 W COB (chip-on-board) Dim to warm (homogenous color mix)
Flash rate:	1 - 14 Hz
DMX channels:	1; 4; 4; 8; 10; 12
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	1 x temperature-controlled fan
Control:	DMX; RDM; stand-alone; master/slave function
Fixtures available for:	Light´J; Light Captain
Projection:	Flicker-free
DMX features:	RDM For bidirectional communication over the DMX line
DMX fail mode:	Hold; blackout
Beam angle:	73°
Beam angle (1/2 peak):	73°
Beam angle (1/10 peak):	99°
Color temperature:	2700K
Color rendering index (CRI):	81 Ra
Luminous flux maintenance:	6.7
Housing color:	Black
Attachment system:	Omega bracket
Display type:	Multicolor LCD display
Diameter mounting holes:	Ø11mm
Use of brands:	Built with SEETRONIC connector
Material:	Aluminum casting
Dimensions:	Length: 22.3 cm Width: 25.5 cm

	Height: 28.7 cm
Weight:	5.43 kg
Noise classification:	Class 0 (no noise at all) depending on mode used
Attachment system:	Mounting bracket
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 1 x omega bracket
- 1 x mounting bracket
- 2 x screw
- 2 x washer