

EUROLITE Audience Blinder 2x100W LED COB 3200K

Audience blinder, wide beam 2 x 100 W COB LED (warm white)

Art. No.: 41606120

GTIN: 4026397455243



The article is no longer in our assortment.

Features:

- 3200 K color temperature
- 1, 2 or 4 DMX channels selectable for various applications
- Each LED can be controlled individually
- Functions: strobe effect with variable speed, dimmer, Master/Slave
- Different dimmer curves and dimmer speed adjustable
- DMX-controlled operation or stand-alone operation with Master/Slave function
- For use on stages, catwalks and crossbeam systems
- Comfortable addressing and setting via control panel with LC display and four operating buttons
- Locking possibility at the mounting bracket
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller
- 2 powerful LEDs 100 W COB (chip-on-board) warm white (WW)
- Dimmer
- Strobe effect
- Control via DMX
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- With a beam angle of 60°

Logistic

EAN / GTIN: 4026397455243

Weight: 4,95 kg

Length: 0.47 m

Width: 0.20 m

Height: 0.29 m

Technical specifications:

Power supply: 230 V AC, 50 Hz

Power consumption: 260 W

| | |
|-------------------------|---|
| IP classification: | IP20 |
| Power connection: | Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x PowerCON (gray), mounting version |
| Lamp type: | LED lamp |
| LED: | 2 x 100 W COB (chip-on-board) warm white (WW) |
| Color temperature: | 3200K |
| Flash rate: | 1 - 20 Hz |
| Equipment: | Dimmer |
| DMX channels: | 1; 2; 4 |
| Control: | DMX |
| Preprogrammed in: | Light`J; LED PC-Control 512; Light Captain |
| Beam angle: | 60° |
| Beam angle (1/2 peak): | 60° |
| Housing color: | Black |
| Dimensions: | Width: 42 cm Depth: 14 cm Height: 24 cm |
| Weight: | 4,50 kg |
| DMX channels: | 1/2/4 |
| DMX connection: | 5-pin and 3-pin XLR |
| Flash-rate: | 20 Hz |
| LED number: | 2 |
| LED type: | Array 100 W, white |
| Color temperature: | 3200 K |
| Beam angle: | 60° |
| Dimensions (L x W x H): | 140 x 420 x 240 mm |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |