

EUROLITE AKKU Multiflood IP 8x10W RGBW Wash CRMX

Art. No.: 41606258

Silent battery-powered IP65 floodlight with RGBW LEDs, CRMX, diffuser cover, barn doors, IR remote control

GTIN: 4026397727562



List price: 950.81 €

incl. 19% VAT.

Features:

- Silent operation
- Control via DMX; W-DMX by wireless solution; CRMX by LumenRadio; Master/slave function; RDM; stand-alone; IR remote control
- Integrated wireless receiver for CRMX operation
- Additional frost filter provides a wide, soft and homogeneous light
- 4 barn doors to avoid blinding the audience and for protection during transport
- 8 powerful LEDs 10 W high-power 4in1 QCL RGBW (homogenous color mix)
- 3 buttons on the remote control for saving your own settings
- Emergency lighting function in case of power failure; color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) with adjustable response; white balance
- 36 integrated show programs
- Strobe effect
- With a beam angle of 10°
- Flicker-free
- The device is cooled by passive convection cooling
- With Mounting bracket; with Omega bracket
- OLED display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use
- With pressure compensation membrane
- With a KENSINGTON LOCK theft protection
- For application areas such as: Stage; architecture; mobile use; Rental
- Battery operation up to 9h depending on program used
- Direct color selection for 15 preset colors
- Preprogrammed in LED PC-Control 512; Light'J

Logistic

EAN / GTIN: 4026397727562

Weight: 8,75 kg

Length: 0.37 m

Width: 0.27 m

Height: 0.30 m

- Display of the remaining battery life for the current setting
- Charge status indicator
- Application possibility: Suspended; on stand; standing

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x remote control, 1 x diffusor cover, 1 x omega bracket, 1 x barndoor, 1 x declaration of conformity

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug Battery/battery pack
Power output:	1 x IP T-Con (F) mounting version
Battery pack:	Battery operation up to 9h depending on program used Recharging time 4,5h
Lamp type:	LED lamp
LED:	8 x 10 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 11
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	DMX; W-DMX by wireless solution; CRMX by LumenRadio; Master/slave function; RDM; stand-alone; IR remote control
Preprogrammed in:	LED PC-Control 512; Light´J
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle:	10°
Beam angle (1/2 peak):	10° Frost filter 25°
Beam angle (1/10 peak):	25° Frost filter 55°
Housing color:	Black
Attachment system:	Mounting bracket Omega bracket
Display type:	OLED display
Display:	Battery runtime calculation , charge status indicator
Theft protection:	KENSINGTON LOCK
Dimensions:	Length: 31,9 cm Width: 14 cm Height: 24,8 cm
Weight:	7,85 kg
Noise classification:	Class 0 (no noise at all)

Remote control	
Battery:	1 x Button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting