

EUROLITE LED IP Atmo Bar 10

Weather-proof blinder bar with pixel control and colored atmospheric light in the reflector

Art. No.: 41606410

GTIN: 4026397719611



List price: 1069.81 €

incl. 19% VAT.

Features:

- 10 powerful LEDs 24 W COB (chip-on-board) CW/WW (homogenous color mix)
 LEDs controlled separately
- 200 powerful LEDs 0,2 W SMD 3528 3in1 TCL RGB (homogenous color mix)
10 segments controlled separately
- Variable color temperature 1800 K - 6000 K
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; dimmer curves with adjustable response; white balance adjustable
- Strobe effect
- 10 integrated show programs
- The device is cooled by low-noise cooling fan
- Control via stand-alone; Master/slave function; DMX; ArtNet; RDM
- Preprogrammed in Light Captain; LED PC-Control 512
- Flicker-free
- With a beam angle of 28°
- With Mounting bracket; with Omega bracket
- OLED display
- Mains input and output for power linking up to 4 units
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Clubs/dancing school; Stage; Rental
- Very quiet working noise
- Application possibility: Suspended

Package contents

- 1 x bar, 1 x user manual, 1 x power cord, 2 x omega bracket, 1 x xLR cable

Logistic

EAN / GTIN: 4026397719611

Weight: 11,85 kg

Length: 1.10 m

Width: 0.28 m

Height: 0.25 m

Technical specifications:

| | |
|-------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 315 W |
| IP classification: | IP65 |
| Protection class: | Protection class I |
| Power connection: | Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided) |
| Power output: | IP T-Con (F) mounting version |
| Lamp type: | LED lamp |
| LED: | 10 x 24 W COB (chip-on-board) CW/WW (homogenous color mix) 200 x 0,2 W SMD 3528 3in1 TCL RGB (homogenous color mix) |
| Color temperature: | 1800K - 6000K adjustable |
| DMX channels: | 10; 14; 20; 50; 59 |
| DMX input: | 3-pin XLR (M) mounting version IP |
| DMX output: | 3-pin XLR (F) mounting version IP |
| Cooling: | Low-noise cooling fan |
| Control: | Stand-alone; Master/slave function; DMX; ArtNet; RDM |
| Preprogrammed in: | Light Captain; LED PC-Control 512 |
| Projection: | Flicker-free |
| Beam angle: | 28° |
| Beam angle (1/2 peak): | 28° |
| Beam angle (1/10 peak): | 63 |
| Housing color: | Black |
| Attachment system: | Mounting bracket 2x Omega bracket |
| Display type: | OLED display |
| Connections: | 2 x RJ-45 E-Con (F) mounting version |
| Dimensions: | Length: 1,01 m Depth: 12,5 cm Height: 24 cm |
| Weight: | 10,50 kg |
| Noise classification: | Class 1 (very slight noise, suitable for noise-sensitive environments) |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |