

EUROLITE LED PAR-30 3CT bi

LED spotlight with three adjustable color temperatures and high color rendering index

Art. No.: 41607041

GTIN: 4026397692112



List price: 89.13 €

incl. 19% VAT.

Features:

- 1 powerful LED 16 W COB (chip-on-board) 2in1 BCL CW/WW
 - The device is cooled by passive convection cooling
 - Control via Quick select potentiometer for brightness and color temperature
 - Flicker-free
 - With a beam angle of 20°
 - Very high color rendering index (CRI)
 - With Mounting bracket
 - Available in various colors
 - Silent operation
 - For application areas such as: Trade fair and shop fitting; video and photography; Installation; restaurants, bars and hotels
 - Dimmable
 - Direct color temperature selection for 3 preset values
 - Dimmer electronic
 - Application possibility: Suspended; on stand
- Package contents**
- 1 x spotlight, 1 x filter frame, 1 x user manual

Logistic

EAN / GTIN: 4026397692112

Weight: 0,88 kg

Length: 0.14 m

Width: 0.14 m

Height: 0.27 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: Max. 18,5 W

IP classification: IP20

Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable length:	Approx. 0,4 m
Lamp type:	LED lamp
Lamp specification:	Dimmable
LED:	1 x 16 W COB (chip-on-board) 2in1 BCL CW/WW
Color temperature:	3000K; 4000K; 5000K
Cooling:	Passive convection cooling
Control:	Quick select potentiometer for brightness and color temperature
Projection:	Flicker-free
Beam angle:	20°
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	35°
Color rendering index (CRI):	90 Ra
Illuminance in Lux (lx):	3000 K 1m: 4483 lx, 3m: 582 lx, 6m: 156 lx 4000 K 1m: 4908 lx, 3m: 634 lx, 6m: 166 lx 5000 K 1m: 5049 lx, 3m: 646 lx, 6m: 170 lx
Lamp life:	15000 h
Luminous flux:	1300 lm
Housing color:	Black
Attachment system:	Mounting bracket
Material:	Aluminum
Slot for spot length:	12,8 cm x 12,8 cm
Dimensions:	Length: 24 cm Width: 14,7 cm Height: 20 cm
Weight:	800 g
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	G
Mounting bracket	
Diameter mounting holes:	2 x Ø10mm
Material:	Aluminum, 3 mm
Dimensions:	Width: 13 cm Depth: 2 cm Height: 13 cm
Filter frame	
Shape:	Octagonal
Material:	Aluminum, 0,8 mm
Dimensions:	Width: 12,6 cm Height: 12,6 cm Diameter: Ø 9,4 cm