

EUROLITE LED PAR-56 COB RGB 25W bk

PAR spot with 25 W COB LED (RGB) & adjustable beam angle (60°/20°)

Art. No.: 41607215

GTIN: 4026397533941



The article is no longer in our assortment.

Features:

- Equipped with one powerful 25 W COB LED with RGB colors
- Functions: stepless RGB color mixture, solid colors, built-in programs, dimmer, strobe effect, Master/Slave operation
- Dimmer speed (step response) adjustable
- Operable in stand-alone mode, via DMX interface or via IR remote control
- Controllable via IR remote control; included in the delivery
- Adjustable microphone sensitivity via Control Board
- Different beam angles (from approx. 60° to approx. 20°) possible via included lens
- Easy installation
- Ideal as floor spot via additional bracket
- Locking possibility at the brackets
- Comfortable addressing and setting via Control Board with LED display and three operating buttons
- Ready for connection via power cord with safety plug
- Switch-mode power supply for operation between 100 and 240 Volts
- Available in silver or black
- 1 powerful LED 25 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
- Strobe effect
- Control via stand-alone; DMX; Sound to light via Microphone
- Preprogrammed in Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE
- Flicker-free
- With a beam angle of 20°

Package contents

- 1 x spotlight, 1 x remote control, 1 x user manual, 1 x lens, 1 x battery

Logistic

EAN / GTIN: 4026397533941

Weight: 2,10 kg

Length: 0.21 m

Width: 0.21 m

Height: 0.31 m

Technical specifications:

| | |
|-------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 25 W |
| IP classification: | IP20 |
| Power connection: | Fixed power supply cord with safety plug |
| Lamp type: | LED lamp |
| LED: | 1 x 25 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix) |
| DMX channels: | 3; 5 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Control: | Stand-alone; DMX; Sound to light via Microphone |
| Preprogrammed in: | Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE |
| Projection: | Flicker-free |
| Beam angle: | 20° |
| Beam angle (1/2 peak): | With fresnell 20° 60° |
| Beam angle (1/10 peak): | With fresnell 28° 101° |
| Housing color: | Black |
| Dimensions: | Width: 22 cm Depth: 17 cm Height: 24,5 cm |
| Weight: | 1,88 kg |
| Noise classification: | Class 2 (slight noise) |
| Remote control | |
| Battery: | 1 x Button cell 3.0 V CR2025 lithium manganese built-in |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |