# eurolite®

## EUROLITE LED ML-46 COB RGBAW 50W Floor bk

ML spot with 50 W COB LED and RGBAW color mixing

Art. No.: 41607311 GTIN: 4026397541465









## The article is no longer in our assortment.

#### Features:

- Equipped with a 50 W LED with RGBAW colors
- HSV, 5, 7, 8 or 11 DMX channels selectable
- Functions: static colors, RGBAW color mixture, automatic color change, internal programs and user defined auto programs, user defined color presets, dimmer and strobe settings, power limitation
- Adjustable white balance
- Dimmer speed (step response) adjustable
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Color presets can be called up via DMX controller
- Strobe effect with adjustable speed
- Beam angle approximately 22°
- Comfortable addressing and setting via Control Board with LED display and four operating buttons
- Ideal as floor spot via additional bracket
- Locking possibility at the brackets
- Optional color filter frame and barndoors available
- Ready for connection with power cord and safety plug
- Switch-mode power supply for operation between 100 and 240 Volts
- Available in silver or in black
- 1 powerful LED 50 W COB (chip-on-board) 5in1 PCL RGBWA (homogenous color mix)
- Strobe effect
- Control via DMX; Sound to light via Microphone
- Preprogrammed in Light'J; LED PC-Control 512
- Flicker-free
- With a beam angle of 22°
  Package contents

#### Logistic

EAN / GTIN: 4026397541465 Weight: 3,00 kg Length: 0.26 m Width: 0.26 m Heigth: 0.31 m

### **Technical specifications:**

| Power consumption:      | 60 W  |
|-------------------------|---|
| IP classification:      | IP20  |
| Power connection:       | Fixed power supply cord with safety plug                              |
| Lamp type:              | LED lamp  |
| LED:                    | 1 x 50 W COB (chip-on-board) 5in1 PCL RGBWA<br>(homogenous color mix) |
| Flash rate:             | 0 - 17 Hz   |
| DMX channels:           | 5; 7; 8; 11; 3 (HSV hue/saturation/value)                             |
| DMX input:              | 1 x 3-pin XLR (M) mounting version                                    |
| DMX output:             | 1 x 3-pin XLR (F) mounting version                                    |
| Control:                | DMX; Sound to light via Microphone                                    |
| Preprogrammed in:       | Light J; LED PC-Control 512   |
| Projection:             | Flicker-free  |
| Beam angle:             | 22°   |
| Beam angle (1/2 peak):  | 22°   |
| Beam angle (1/10 peak): | 52°   |
| Housing color:          | Black   |
| Dimensions:             | Width: 23,5 cm  |
|                         | Depth: 22 cm  |
|                         | Height: 23 cm   |
| Weight:                 | 2,50 kg   |
| Legal specifications    |   |
| Special product:        | Not designed for household room illumination                          |
| Intended use:           | Show effect lighting  |
|                         |   |