

## EUROLITE LED ML-56 COB RGB 100W Floor sil

ML spot with 100 W COB LED and RGB color mixing

Art. No.: 41607321

GTIN: 4026397588279



**The article is no longer in our assortment.**

### Description:

ML spot with 100 W COB LED and RGB color mixing

The Eurolite LED ML-56 spotlight is equipped with a 100 Watts Chip-on-Board (COB) LED in RGB colors, which ensure homogeneous color mixing. It is suitable for use in theatres, on large stages as a front spotlight and for mobile use. Because of the additional stand bracket, the ML-56 can also be used as a floor spot.

The effect spotlight comes with a variety of functions: Automatic color change, internal and user-defined programs, dimmer and strobe effect with variably adjustable speed. The flicker-free projection even makes it possible to use the spotlight for video recording.

You can control the Eurolite LED ML-56 COB via DMX with master/slave function or in standalone mode. In addition, the built-in microphone allows you to operate the spotlight via music control. Comfortable addressing and setting is possible via the Control Board with four operating keys and LED display.

### Features:

- Equipped with one COB 100 W LED in RGB colors
- Stepless color blend, color change, preset colors, dimmer and strobe effect
- Adjustable white balance
- Dimmer speed (step response) adjustable
- Stand-alone, master/slave and DMX mode
- Color presets can be called up via DMX controller
- Strobe effect with adjustable speed
- 40° beam angle

### Logistic

EAN / GTIN: 4026397588279

Weight: 4,00 kg

Length: 0.29 m

Width: 0.29 m

Height: 0.39 m

- Control panel with LED display for easy configuration
  - Additional bracket for floor use
  - 2 swivel mounting brackets
  - With color filter frame
  - Optional barndoors available
  - Ideal for theatres, large stages as pre-stage spot and mobile use
  - Various versions available
  - 1 powerful LED 100 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
  - Strobe effect
  - The device is cooled by cooling fan
  - Control via DMX; Sound to light via Microphone
  - Preprogrammed in EASY SHOW 1; Light´J; LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
  - Flicker-free
  - With a beam angle of 40°
- Package contents**
- 1 x filter frame

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	90 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable length:	Approx. 1,2 m
Lamp type:	LED lamp
LED:	1 x 100 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
Flash rate:	0 - 17 Hz
DMX channels:	3; 3 (HSV hue/saturation/value); 5; 6; 9
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; Sound to light via Microphone
Preprogrammed in:	EASY SHOW 1; Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
Projection:	Flicker-free
Beam angle:	40°
Beam angle (1/2 peak):	40°
Beam angle (1/10 peak):	82°
Housing color:	Silver
Dimensions:	Width: 31 cm Depth: 26 cm Height: 30 cm
Weight:	3,41 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Legal specifications	
Special product:	Not designed for household room illumination

Intended use:

Show effect lighting

---