

EUROLITE AKKU Bar-3 Glow QCL Flex QuickDMX

Tiltable battery-powered LED bar and mood light with 4in1 LEDs and QuickDMX

Art. No.: 41700117 GTIN: 4026397691337



List price: 236.81 €

incl. 19% VAT.

Features:

- 90° tiltable bar with 3 high-power 8 W RGBW LEDs (4in1) and removable frost filter
- Mood light with milky front screen provides a pleasantly soft light with 15 SMD RGBW LEDs (4in1)
- Integrated QuickDMX transceiver for wireless DMX control
- Cordless, flexible and versatile
- Battery operation up to 13h depending on program used
- Integrated automatic charging of the battery and status indicator
- 15 powerful LEDs 0,25 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
- 3 powerful LEDs 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic;
 Dimmer speed (step response) adjustable
- Strobe effect
- Integrated show programs
- Direct color selection for 35 preset colors
- The device is cooled by passive convection cooling
- Control via IR remote control; stand-alone; QuickDMX; master/slave function; sound to light via microphone
- Preprogrammed in Light'J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 11°
- Multicolor LCD display
- With a KENSINGTON LOCK theft protection
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; small rental
- Silent operation

Logistic

EAN / GTIN: 4026397691337

Weight: 2,20 kg Length: 0.39 m Width: 0.17 m Heigth: 0.14 m

- Application possibility: Standing; suspended; on stand
 - Package contents
- 1 x device, 1 x external mains adapter, 1 x remote control, 1 x omega bracket, 2 x screw, 1 x frost filter, 1 x battery, 1 x declaration of conformity, 1 x user manual

Technical specifications:

| Power consumption: | 30 W |
|-------------------------|--|
| IP classification: | IP20 |
| Protection class: | Protection class III |
| Power connection: | Battery/battery pack |
| Battery pack type: | 1 x lithium ion 11,10 V, 5200 mAh, 57,72 Wh |
| Battery pack: | Battery operation up to 13h depending on program used |
| | Recharging time 3h |
| Lamp type: | LED lamp |
| LED type: | 15 x 0,25 W SMD 5050 4in1 QCL RGBW (homogenous color mix) |
| | 3 x 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix) |
| DMX channels: | 3; 7; 8; 9; 11 |
| Cooling: | Passive convection cooling |
| Control: | IR remote control; stand-alone; QuickDMX; master/slave function; sound to light via microphone |
| Preprogrammed in: | Light'J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief |
| Projection: | Flicker-free |
| Carrier frequency: | 2,4 GHz |
| Beam angle: | 11° |
| Beam angle (1/2 peak): | 11° |
| Beam angle (1/10 peak): | 30° |
| Housing color: | Black |
| Display type: | Multicolor LCD display |
| Theft protection: | KENSINGTON LOCK |
| Dimensions: | Length: 24,6 cm Width: 9,5 cm Height: 10,5 cm |
| Weight: | 1,93 kg |
| Noise classification: | Class 0 (no noise at all) |
| External mains adapter | |
| Power supply: | 100-240 V AC, 50/60 Hz 12,6V DC 2000 mA |
| Protection class: | Protection class II |
| | Mains input via coaxial power connector (M) mounting version power supply cord with Euro |
| Power connection: | plug (provided) |

| Battery: | 1 x button cell 3.0 V CR2032 lithium manganese built-in | |
|----------------------|---|--|
| Legal specifications | egal specifications | |
| Special product: | Not designed for household room illumination | |
| Intended use: | Show effect lighting | |