

EUROLITE AKKU Bar-3 Glow QCL Flex QuickDMX

Tilttable battery-powered LED bar and mood light with 4in1 LEDs and QuickDMX

Art. No.: 41700117

GTIN: 4026397691337



Features:

- 90° tilttable bar with 3 high-power 8 W RGBW LEDs (4in1) and removable frost filter
- Mood light with milky front screen provides a pleasantly soft light with 15 SMD RGBW LEDs (4in1)
- Integrated QuickDMX transceiver for wireless DMX control
- Cordless, flexible and versatile
- Battery operation up to 13h depending on program used
- Integrated automatic charging of the battery and status indicator
- 15 LEDs 0.25 W SMD 5050 4in1 RGBW (homogenous color mix)
- 3 LEDs 8 W SMD 9080 4in1 RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable
- Atmospheric effect
- Integrated show programs
- Direct color selection for 35 preset colors
- The device is cooled by passive convection cooling
- Control via IR remote control; stand-alone; QuickDMX; master/slave function; sound to light via microphone
- Flicker-free
- With a beam angle of 11°
- Multicolor LCD display
- With a KENSINGTON LOCK theft protection
- For application areas such as: Clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397691337

Weight: 2,20 kg

Length: 0.39 m

Width: 0.17 m

Height: 0.14 m

Technical specifications:

Power consumption:	30 W
Protection class:	Protection class III
Power connection:	Battery/battery pack
Battery pack type:	1 x lithium ion 11.10 V, 5200 mAh, 57.72 Wh
Battery pack:	Battery operation up to 13h depending on program used Recharging time 3h
Lamp type:	LED lamp
LED type:	15 x 0.25 W SMD 5050 4in1 RGBW (homogenous color mix) 3 x 8 W SMD 9080 4in1 RGBW (homogenous color mix)
DMX channels:	3; 7; 8; 9; 11
Cooling:	Passive convection cooling
Control:	IR remote control; stand-alone; QuickDMX; master/slave function; sound to light via microphone
Fixtures available for:	Light J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Carrier frequency:	2.4 GHz
Beam angle (1/2 peak):	11°
Beam angle (1/10 peak):	30°
Housing color:	Black
Display type:	Multicolor LCD display
Theft protection:	KENSINGTON LOCK
Dimensions:	Length: 24.6 cm Width: 9.5 cm Height: 10.5 cm
Weight:	1.93 kg
Noise classification:	Class 0 (no noise at all)
Power supply:	100-240 V AC, 50/60 Hz 12.6V DC 2000 mA
Protection class:	Protection class II
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with Euro plug (provided)
Cable length:	Approx. 1.4 m
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

- 1 x device
- 1 x external mains adapter
- 1 x remote control
- 1 x omega bracket
- 2 x screw
- 1 x frost filter
- 1 x battery
- 1 x declaration of conformity
- 1 x user manual