

EUROLITE AKKU TL-3 TCL Trusslight

Spotlight with 3 x 3 W 3in1 LED (RGB) for lighting within trussing

Art. No.: 41700500

GTIN: 4026397516579



Description:

The AKKU TL-3 TCL is a spotlight equipped with 3 bright 3-watt RGB LEDs (3in1) designed for lighting within trussing. It is wireless and battery-run (battery life 6.5 hours) and its small size makes it a great fit for many 3- and 4-point trussing systems.

You can choose from a variety of different functions such as static colors, continuous RGB color mixture, internal programs, dimmer effects as well as strobe effects with adjustable speed.

The device can either be controlled via DMX or the supplied wireless remote control (Eurolite IR-7).

All of these features make the AKKU TL-3 TCL the perfect choice for booth construction, stages and any kind of truss.

Features:

- Compact and bright, making it perfect for truss installation
- Cordless, flexible and versatile
- Equipped with 3 x 3 W TCL LED in red, green and blue
- Operation via mains connection or built-in rechargeable lithium-ion battery with up to 6.5 hours operating time
- Integrated automatic charging of the battery with indicator
- Controllable via EUROLITE IR-7 remote control; included in the delivery
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 3, 5 or 8 DMX channels selectable
- Functions: static colors, stepless RGB color mixture, internal programs, dimmer, strobe effect with variable speed, sound-control, Master/Slave operation
- Dimmer speed (step response) adjustable
- Adjustable microphone sensitivity

Logistic

EAN / GTIN: 4026397516579

Weight: 1,50 kg

Length: 0.18 m

Width: 0.17 m

Height: 0.20 m

- Addressing via control panel with 4-digit LED display
 - Ideal for booth construction, stages and any kind of truss
 - Ideal for ALUTRUSS 3-POINT SYSTEM DECOLOCK DQ3
 - Hanging as well as standing installation possible
 - Switch-mode power supply for operation between 100 and 240 volts
 - Ready for connection via included power cable with safety power plug
 - Feed-through output allows to power up to 8 devices
 - 3 LEDs 3 W SMD 8072 3in1 R/G/B (homogenous color mix)
 - Control via DMX; stand-alone; sound to light via microphone
 - Flicker-free
 - With a beam angle of 16°
- device**
- Cordless, flexible and versatile
 - Battery operation up to 6.5h depending on program used

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	19.00 W
Power connection:	Battery/battery pack Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	3 x 3 W SMD 8072 3in1 R/G/B (homogenous color mix)
Flash rate:	0 - 30 Hz
DMX channels:	3; 5; 8
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; stand-alone; sound to light via microphone
Fixtures available for:	Light J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	34°
Housing color:	Black
Dimensions:	Width: 12.1 cm Depth: 10.8 cm Height: 13.6 cm
Weight:	1.35 kg
Battery pack type:	1 x lithium ion 11.1 V, 4400 mAh, 48.84 Wh
Battery pack:	Battery operation up to 6.5h depending on program used Recharging time 4.5h
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x device

1 x remote control