

EUROLITE AKKU TL-3 TCL Trusslight QuickDMX wh

Spot for lighting within trussing, 3 x 3 W 3in1 LED, QuickDMX transceiver

Art. No.: 41700503

GTIN: 4026397666489



List price: 213.01 €

incl. 19% VAT.

Features:

- Compact and bright
 - Ideal for ALUTRUSS DECOLOCK DQ3 3-point system
 - Integrated QuickDMX transceiver for wireless DMX control
 - Threaded inserts for suspended installation
 - Battery operation up to 16h depending on program used
 - 3 powerful LEDs 3 W high-power 3in1 TCL RGB (homogenous color mix)
 - Dimmer electronic; color blend stepless; color change adjustable; Dimmer speed (step response) adjustable
 - Strobe effect
 - The device is cooled by passive convection cooling
 - Control via IR remote control; DMX; QuickDMX; Sound to light via Microphone; stand-alone
 - Flicker-free
 - With a beam angle of 11°
 - For application areas such as: Small rental; Wedding/gala/events; mobile djs / entertainer; Stage
 - Preprogrammed in Light´J; LED PC-Control 512; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
 - Silent operation
 - Cordless, flexible and versatile
 - Mains input and output for power linking up to 8 units
 - Application possibility: Standing; suspended
- Package contents**
- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 1 x declaration of conformity

Logistic

EAN / GTIN: 4026397666489
Weight: 1,46 kg
Length: 0.16 m
Width: 0.16 m
Height: 0.19 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	25 W
IP classification:	IP20
Power connection:	Battery/battery pack Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Cable length:	Approx. 1,2 m
Power output:	1 x IEC connector (F) mounting version
Battery pack type:	1 x lithium ion 11,1 V, 4400 mAh, 48,84 Wh
Battery pack:	Battery operation up to 16h depending on program used Recharging time 3h
Lamp type:	LED lamp
LED:	3 x 3 W high-power 3in1 TCL RGB (homogenous color mix)
Flash rate:	0 - 23 Hz
DMX channels:	3; 5; 8
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	IR remote control; DMX; QuickDMX; Sound to light via Microphone; stand-alone
Preprogrammed in:	Light J; LED PC-Control 512; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle:	11°
Beam angle (1/2 peak):	11°
Beam angle (1/10 peak):	24°
Housing color:	White
Dimensions:	Width: 12,1 cm Depth: 10,8 cm Height: 14,5 cm
Weight:	1,30 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x Button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting