

EUROLITE AKKU TL-3 QCL RGB+UV Trusslight

Battery-powered trusslight with RGB+UV LEDs and IR remote control

Art. No.: 41700510

GTIN: 4026397683783



List price: 165.41 €

incl. 19% VAT.

Features:

- Ideal for ALUTRUSS DECOLOCK DQ3 3-point system
- Threaded inserts for suspended installation
- Battery operation up to 8h depending on program used
- 3 powerful LEDs 4 W high-power 4in1 QCL RGB/UV (homogenous color mix)
- Integrated show programs
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 10°
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; white balance; Energy-saving mode
- Strobe effect
- Direct color selection for 20 preset colors
- Silent operation
- Preprogrammed in Light Captain; EASY SHOW 2; EASY SHOW 3; Light J
- Mains input and output for power linking up to 8 units
- Cordless, flexible and versatile
- Integrated automatic charging of the battery and status indicator
- Rubber feet
- For application areas such as: Stage; mobile djs / entertainer; small rental; Rental
- Application possibility: Standing; suspended

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

Logistic

EAN / GTIN: 4026397683783

Weight: 1,38 kg

Length: 0.15 m

Width: 0.14 m

Height: 0.17 m

Technical specifications:

| | |
|-------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| IP classification: | IP20 |
| Protection class: | Protection class III |
| Power connection: | Battery/battery pack built-in Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output: | IEC connector (F) mounting version |
| Fuse: | F 1 A Fuse replaceable |
| Battery pack type: | 1 x lithium ion 11,1 V, 2200 mAh, 24,42 Wh |
| Battery pack: | Battery operation up to 8h depending on program used Recharging time 2,5h |
| Lamp type: | LED lamp |
| LED: | 3 x 4 W high-power 4in1 QCL RGB/UV (homogenous color mix) |
| Flash rate: | 0 - 20 Hz |
| DMX channels: | 2; 4; 5; 6; 9 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; DMX; IR remote control; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Preprogrammed in: | Light Captain; EASY SHOW 2; EASY SHOW 3; Light J |
| Projection: | Flicker-free |
| Beam angle: | 10° |
| Beam angle (1/2 peak): | 10° |
| Beam angle (1/10 peak): | 33° |
| Housing color: | Black |
| Transport aid: | Rubber feet |
| Dimensions: | Width: 12,22 cm Depth: 10,8 cm Height: 14,3 cm |
| Weight: | 1,26 kg |
| Noise classification: | Class 0 (no noise at all) |
| Remote control | |
| Battery: | 1 x Button cell 3.0 V CR2025 lithium manganese built-in |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |