

## EUROLITE AKKU IP UP-4 QCL Spot QuickDMX

Weather-proof (IP65), Uplight with 4 x 10 W 4in1 LED, QuickDMX & diffusor disk

Art. No.: 41700542

GTIN: 4026397629606



**List price: 474.81 €**

incl. 19% VAT.

### Features:

- Integrated QuickDMX transceiver for wireless DMX control
- Additional frost filter provides a wide, soft and homogeneous light
- Battery operation up to 16h depending on program used
- 4 powerful LEDs 10 W high-power 4in1 QCL RGBW (homogenous color mix)
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; QuickDMX; Sound to light via Microphone; IR remote control; Master/slave function
- Flicker-free
- With a beam angle of 7°
- LCD display
- Suitable for outdoor use IP65
- With a KENSINGTON LOCK theft protection
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; small rental
- Dimmer speed (step response) adjustable; Dimmer electronic; color blend stepless; color change adjustable; colors preset
- Preprogrammed in Light´J; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
- Cordless, flexible and versatile
- Integrated automatic charging of the battery and status indicator
- With bracket for floor use
- Silent operation
- Application possibility: Standing

### Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x diffusor cover, 1 x remote control, 1 x battery, 2 x knurled screw, 1 x mounting bracket, 2 x screw, 1 x declaration of conformity

### Logistic

EAN / GTIN: 4026397629606

Weight: 4,71 kg

Length: 0.22 m

Width: 0.22 m

Height: 0.23 m

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Battery/battery pack Mains input via IP P-Con (Power in) yellow mounting version power supply cord with safety plug (provided)
Cable length:	Approx. 1,2 m
Battery pack type:	1 x lithium ion 14,8 V, 7800 mAh, 115,44 Wh
Battery pack:	Battery operation up to 16h depending on program used Recharging time 3h
Lamp type:	LED lamp
LED:	4 x 10 W high-power 4in1 QCL RGBW (homogenous color mix)
DMX channels:	3; 4; 6; 8; 10
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; QuickDMX; Sound to light via Microphone; IR remote control; Master/slave function
Preprogrammed in:	Light J; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle:	7°
Beam angle (1/2 peak):	7°
Beam angle (1/10 peak):	20°
Housing color:	Black
Attachment system:	Bracket for floor use
Display type:	LCD display
Theft protection:	KENSINGTON LOCK
Dimensions:	Width: 15 cm Depth: 18 cm Height: 19,8 cm
Weight:	4,44 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x Button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination

Intended use:

Show effect lighting

---