

## EUROLITE AKKU UP-4 QCL Spot

Bright Uplight with 4 x 8 W 4in1 LED

Art. No.: 41700550

GTIN: 4026397516425



**The article is no longer in our assortment.**

### Features:

- Compact and bright
  - Equipped with 4 x 8 W QCL LED in red, green, blue and white
  - Operation via mains connection or built-in rechargeable lithium-ion battery with up to 8.5 hours operating time
  - Integrated automatic charging of the battery with indicator
  - Controllable via EUROLITE IR-7 remote control; included in the delivery
  - With integrated folding foot for flexible placement
  - DMX-controlled operation or stand-alone operation with Master/Slave function
  - 4, 6 or 10 DMX channels selectable
  - Functions: static colors, stepless RGBW color mixture, internal programs, dimmer, strobe effect with variable speed, sound-control
  - Dimmer speed (step response) adjustable
  - Adjustable microphone sensitivity
  - Addressing via control panel with 4-digit LED display
  - Switch-mode power supply for operation between 100 and 240 volts
  - Ready for connection via included power cable with safety power plug
  - Feed-through output allows to power up to 8 devices
  - DMX control via any standard DMX controller
  - 4 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
  - The device is cooled by passive convection cooling
  - Control via DMX; stand-alone; Sound to light via Microphone
  - Preprogrammed in Light 'J; LED PC-Control 512; Light Captain
  - Flicker-free
  - With a beam angle of 13°
- device**
- Cordless, flexible and versatile

### Logistic

EAN / GTIN: 4026397516425

Weight: 3,20 kg

Length: 0.23 m

Width: 0.20 m

Height: 0.27 m

- Battery operation up to 8,5h depending on program used

**Package contents**

- 1 x device, 1 x remote control

**Technical specifications:**

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	45,00 W
IP classification:	IP20
Power connection:	Battery/battery pack Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED:	4 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
DMX channels:	4; 6; 10
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; Sound to light via Microphone
Preprogrammed in:	Light J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	13°
Beam angle (1/2 peak):	13°
Beam angle (1/10 peak):	28,5°
Housing color:	Black
Dimensions:	Width: 13,8 cm Depth: 14,5 cm Height: 19,1 cm
Weight:	2,90 kg
<b>Device</b>	
Battery pack type:	1 x lithium ion 14,8 V, 6600 mAh, 97,68 Wh
Battery pack:	Battery operation up to 8,5h depending on program used Recharging time 5h
<b>Remote control</b>	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
<b>Legal specifications</b>	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting