eurolite®

EUROLITE AKKU Wash 1 HCL Spot

Handy battery-powered LED washlight with 10 W 6in1 LED

eurolite anna tina sion

The article is no longer in our assortment.

Features:

- Powerful battery-powered LED washlight in small design
- With one bright 6in1 hexacolor LED in the colors red, green, blue, white, amber and UV
- Ideal for mobile use thanks to quick setup and rechargeable li-ion battery pack (up to 6 hours operating time)
- Magnetic base affixes to metal surfaces
- Movable and tiltable mounting bracket and scissor clip for easy attachment to drop ceiling supports
- Controllable via EUROLITE IR-7 remote control; included in delivery
- Functions: static colors, RGBAW+UV color mixture, automatic color change, fading colors, dimmer, strobe effect, sound-control
- Sound-control via built-in microphone
- Adjustable microphone sensitivity
- Charger included in the delivery
- Switch-mode power supply for operation between 100 and 240 volts
- Elegant white metal housing
- Transport bag with integrated multi-charger available as accessory
- The device is cooled by passive convection cooling
- Control via IR remote control; stand-alone
- Flicker-free
- With a beam angle of 22° device
- Cordless, flexible and versatile
- Battery operation up to 6h depending on program used Package contents
- 1 x device, 1 x remote control

Logistic

EAN / GTIN: 4026397539042 Weight: 1,12 kg Length: 0.25 m Width: 0.18 m Heigth: 0.11 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.









Art. No.: 41700620

GTIN: 4026397539042

Technical specifications:

Power consumption:	8,4 W
IP classification:	IP20
Lamp type:	LED lamp
Cooling:	Passive convection cooling
Control:	IR remote control; stand-alone
Projection:	Flicker-free
Beam angle:	22°
Beam angle (1/2 peak):	22°
Beam angle (1/10 peak):	45°
Housing color:	White
Dimensions:	Width: 9,2 cm
	Depth: 12,5 cm
	Height: 20,5 cm
Weight:	0,98 kg
Device	
Battery pack type:	1 x lithium ion 7,4 V, 4400 mAh, 32,56 Wh
Battery pack:	Battery operation up to 6h depending on program used
	Recharging time 5h
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Power supply:	8.4 V, 1.35 A via charger (100-240 V AC, 50/60 Hz)
Battery pack type:	Li-ion 7.4 V, 4400 mAh (32.56 Wh)
Battery operation:	6 hours
Recharging time:	5 hours
Battery remote control:	CR2025 button cell 3 V
Sound-control:	via built-in microphone
LED type:	10 W HCL
LED number:	1
Beam angle:	22°
Dimensions (LxW):	205 x 92 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting