

EUROLITE AKKU IP PAR 14 HCL QuickDMX

IP65 battery-powered spotlight with RGBWA+UV LEDs, QuickDMX, frost filter and IR remote control

Art. No.: 41700800

GTIN: 4026397676167



List price: 712.81 €

incl. 19% VAT.

Features:

- Integrated QuickDMX transceiver for wireless DMX control
- Battery operation up to 26h depending on program used
- 14 powerful LEDs 10 W 6in1 HCL RGBWA/UV (homogenous color mix)
- Frost filter
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- Integrated show programs
- Direct color selection for 27 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; IR remote control; master/slave function; QuickDMX
- Preprogrammed in LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light'J; Colorchief
- Flicker-free
- With a beam angle of 15°
- Variable color temperature 2700 K - 8000 K
- With double bracket
- LCD display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use
- For application areas such as: Mobile use; stage; rental
- Silent operation
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397676167

Weight: 9,10 kg

Length: 0.41 m

Width: 0.36 m

Height: 0.35 m

battery pack

- Cordless, flexible and versatile

Package contents

- 1 x spotlight, 1 x power cord, 1 x XLR cable, 3 x frost filter, 1 x remote control, 2 x screw, 1 x user manual

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Battery/battery pack built-in Via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Power output:	IP T-Con (F) mounting version
Fuse:	5 x 20 mm, T 3 A fuse serviceable
Battery pack:	Battery operation up to 26h depending on program used Recharging time 3h
LED type:	14 x 10 W 6in1 HCL RGBWA/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
Equipment:	Frost filter
DMX channels:	2; 3; 6-1; 6-2; 12
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; IR remote control; master/slave function; QuickDMX
Preprogrammed in:	LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light J; Colorchief
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle:	15°
Beam angle (1/2 peak):	15° 27° 30° 60°
Color temperature:	2700K - 8000K adjustable
Housing color:	Black
Attachment system:	Double bracket
Display type:	LCD display
Material:	Aluminum casting
Dimensions:	Width: 31,7 cm Depth: 22,7 cm Height: 37,0 cm
Weight:	7,85 kg
Noise classification:	Class 0 (no noise at all)
Battery pack	
Battery pack type:	1 x lithium ion 22,2 V, 4400 mAh, 97,68 Wh

Mounting bracket	
Diameter mounting holes:	3 x Ø11mm
Material:	Metal, 3 mm
Power cord	
Cable construction:	3 x 1,0 mm² H05RN-F
Cable length:	Approx. 1,2 m
XLR cable	
Cable length:	Approx. 1,5 m
Plug A:	1 x 3-pin XLR (M)
Plug B:	1 x 3-pin XLR (F)
Frost filter	
Diameter mounting holes:	2 x Ø4mm
Material:	Plastic, 2 mm
Dimensions:	Diameter: Ø 20,5 cm
Remote control	
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting