



Features:

- Professional theatre spot with color filter frame and protective grille
- Impressive light output
- Robust version
- Easy lamp replacement
- Antihalo lens for punctual illumination (light inside the beam is brighter than outside)
- Focus manual
- The device is cooled by passive convection cooling
- Control via plug and play
- With a beam angle of 10° - 42°
- With mounting bracket
- For application areas such as: Stage; decoration; wedding/gala/events; Trade fair and shop fitting; theater; video and photography
- Silent operation

Logistic

EAN / GTIN: 4026397419610
Weight: 9,65 kg
Length: 0.50 m
Width: 0.37 m
Heigh: 0.34 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 2000 W
IP classification:	IP20
Protection class:	Protection class I
Suitable lamp:	Max. 230 V/2000 W lamp envelope GY16
Power connection:	Fixed power supply cord with safety plug

Cable construction:	3 x 1.5 mm² H05SS-F
Cable length:	Approx. 0.9 m
Base:	GY16
Equipment:	Focus manual
Color generation:	Via color filter frame
Cooling:	Passive convection cooling
Control:	Plug and play
Beam angle:	10° - 42°
Beam angle (1/2 peak):	10 - 40°
Beam angle (1/10 peak):	15 - 42°
Housing color:	Black
Attachment system:	Mounting bracket
Material:	Metal; aluminum
Dimensions:	Length: 45 cm Width: 32 cm Height: 40 cm
Weight:	8.85 kg
Noise classification:	Class 0 (no noise at all)
Diameter mounting holes:	4 x Ø12mm
Material:	Metal, 4 mm
Diameter mounting holes:	2 x Ø10mm
Grid size:	20 x 20 mm
Material:	Metal, 0.5 mm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x spotlight
 1 x mounting bracket
 1 x filter frame
 1 x user manual