

EUROLITE PAR-56 Spot CDM150 sil

Long PAR-56 housing for CDM-T 150 discharge lamps

Art. No.: 42000910

GTIN: 4026397426946



Features:

- Rugged metal housing
- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Protective shield is integrated in the tube
- Control via plug and play
- With a beam angle of 55°
- With mounting bracket
- For PAR 56
- For application areas such as: Trade fair and shop fitting; video and photography; advertisement/Shop window

Logistic

EAN / GTIN: 4026397426946

Weight: 4,50 kg

Length: 0.27 m

Width: 0.28 m

Height: 0.46 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
---------------	-----------------

Power consumption:	210 W
--------------------	-------

IP classification:	IP20
--------------------	------

Protection class:	Protection class I
-------------------	--------------------

Power connection:	Fixed power supply cord with safety plug
-------------------	--

Cable length:	Approx. 0.8 m
---------------	---------------

Base:	G-12
-------	------

Lamp type:	Discharge lamp
------------	----------------

Color generation:	Via color filter frame (optional)
-------------------	-----------------------------------

Control:	Plug and play
Beam angle:	55°
Beam angle (1/2 peak):	55°
Housing color:	Silver
Attachment system:	Mounting bracket
Dimensions:	Length: 36 cm Width: 24 cm Height: 32 cm
Weight:	4.00 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x spotlight
1 x filter frame
1 x user manual