

EUROLITE KLS-Kombo Pack 8

Universal mobile light set

Art. No.: 42109548

GTIN:



Features:

- Combines four LED spots and beam effect and four matrix effects
- The standard light system for every small band, solo entertainers and parties
- Set consisting of: 42109781 EUROLITE LED KLS-401 Compact lightset, 51918559 EUROLITE LED MAT-Bar 4x64 Matrix strip, 51918677 EUROLITE LED SCY-200 Beam effect, 60004120 Speaker system stand alu, black, 59007081 EUROLITE STV-3529 Adapter long
- Details to the products:
- KLS-401 Compact lightset
- Complete LED light set with 4 spots
- Compact and easy to transport
- 720 LEDs
- 4 IEC outputs for power supply of further devices
- MAT-Bar 4x64 Matrix strip
- Space-saving solution
- Diverse mounting options; via mounting hole for example
- 256 LEDs
- SCY-200 Beam effect
- Bright fan effect with 6 x 3 W tricolor LEDs
- 1 row of 6 glass lenses
- Each lens can be controlled individually via DMX
- You can find more information under the respective article
- EUROLITE LED KLS-401 Compact Light Set
- ## Bar with 4 spots with 108 LEDs (RGB) each and carrying bag

Complete LED light set with four slimline LED spots
- Crossbar with integrated DMX control unit
- Installation via TV pin for tripods with 28 mm interior diameter
- Ultra-light ideally suited for mobile use

Logistic

- Comes pre-assembled with practical transport bag
- 180 x 10 mm LED per spot (60 x red, 60 x green, 60 x blue)
- Movable and tiltable spotlights
- DMX-controlled operation or stand-alone operation with processor-controlled color change
- Master/Slave operation
- Sound-control via built-in microphone with sensitivity control
- Convenient control possible via optional 4-pedal foot pedal FP-1 or IR remote control
- DMX512 control via regular DMX controller (occupies 15 channels)
- Optimized for control with the optional control panel DMX LED Operator 4
- Via DMX, each spot can be individually controlled
- DMX functions: dimmer, automatic mode, music control, strobe effect
- Addressing and setting via control panel with 4-digit LED display
- Suited for installation on a lighting stand (not included)
- Black lacquered metal version
- Ideal for bands, stages or solo entertainers
- Ready for connection with power cord and safety plug
- 4 IEC outputs for power supply of further devices
- 180 LEDs 10 mm R/G/B
 spots controlled separately
- Control via stand-alone; DMX; foot switch (optional); IR remote control (optional)
- Fixtures available for LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- With a beam angle of 25°
- For further information about this product, please refer to the Data Sheet under "Downloads"
- <p>OMNITRONIC Speaker System Stand alu bk
- <h2 class="featureSatz">High-quality speaker stand</h2>Stable speaker stand for mobile use
- The telescopic tube is additionally fixed with a safety pin
- Adjustable height
- <p>EUROLITE STV-3529 Adapter long
- <h2 class="featureSatz">Massive adapter for 35 mm tube, 28 mm TV spigot, maximum load WLL 100 kg</h2>For stands with telescopic tube 35 mm
- Connection element for cross beam with 28 mm TV spigot
- With M6 and M8 fixation screw
- Heavy version for highest stability
- TV spigot
- <p>EUROLITE LED MAT-Bar 4x64 Matrix bar
- <h2 class="featureSatz">Flower effect bar with 256 LEDs (RGB)</h2>DMX512 control via regular DMX controller (occupies 7 channels)
- The colorful flower beams change their direction of movement at every bass beat in sound controlled mode
- Sound controlled via built-in microphone
- Microphone sensitivity adjustable via rotary control
- Auto mode, speed adjustable via DMX
- Internal programs
- Master/Slave function
- Control panel with 4 buttons and LED display
- Rugged compact housing
- Ready for connection with power cord and plug
- Including mounting bracket and mounting hole (36 mm) with fixation screw for installation on a truss system or stand, and carry bag
- Control via stand-alone; DMX
- Fixtures available for Light´J
- <p>EUROLITE LED SCY-200 Beam Effect
- <h2 class="featureSatz">Classic beam effect as 3in1 version</h2>Beam effect with particularly bright tricolor LEDs (6 x 3 W)
- 1 row with 6 glass lenses
- Each lens can be controlled individually via DMX
- DMX512 control via regular DMX controller (occupies max. 20 channels)
- 7 or 20 DMX channels selectable for numerous applications
- Sound controlled via built-in microphone
- Microphone-sensitivity adjustable via rotary-control
- Strobe effect
- Auto mode
- Internal programs
- Master/Slave function
- Addressing and setting via control panel with 4-digit LED display and three operating buttons

- Additional controlling possibility via the EUROLITE RC-2 remote control (not included in the delivery)
- Ready for connection via IEC power cord with safety plug
- Mounting bracket for installation on a truss system included
- Floor stand for uplighting applications available as accessory
- Ideal for bands, stages or solo entertainers
- Control via sound to light via microphone
- Fixtures available for Light´J
- <p>OMNITRONIC XLR Cable 3-pin 1m bk
- <h2 class="featureSatz">Audio cable with 3-pin XLR connectors</h2>

Technical specifications:

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE LED KLS-401 Compact Light Set

Power supply:	230 V AC, 50 Hz
Power consumption:	55.00 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	180 x 10 mm R/G/B
DMX channels:	15
Control:	Stand-alone; DMX; foot switch (optional); IR remote control (optional)
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Beam angle (1/2 peak):	25°
Housing color:	Black
Dimensions:	Width: 120 cm Depth: 5.5 cm Height: 31 cm
Weight:	9.30 kg
DMX connection:	3-pin XLR
LED type:	10 mm
LED number:	720 (240 red, 240 green, 240 blue)
TV spigot:	D = 28 mm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OMNITRONIC Speaker System Stand alu bk

Maximum carrying capacity:	30 kg
Height:	Maximum: 230 cm Minimum: 140 cm
Type (general stands):	Speaker stand/manual
Material:	Aluminum
Color:	Black
Weight:	3.45 kg
Maximum load:	30 kg
Maximum load (DIN15560):	18 kg
Minimum height:	1.40 m
Maximum height:	2.20 m

EUROLITE STV-3529 Adapter long

Maximum load BGV C1 (8-fold):	50 kg
Maximum load WLL (4-fold):	100 kg
Attachment system:	TV spigot Ø 28mm Ø 35mm
Type (general stands):	Accessory
Material:	Steel, 6 mm, powder-coated
Dimensions:	Width: 8.50 cm Depth: 5 cm Height: 19.50 cm
Weight:	1.50 kg

EUROLITE LED MAT-Bar 4x64 Matrix bar

Power supply:	230 V AC, 50 Hz
Power consumption:	40.00 W
IP classification:	IP20
Lamp type:	LED lamp
Control:	Stand-alone; DMX
Fixtures available for:	Light J
Beam angle (1/2 peak):	15°
Housing color:	Black
Dimensions:	Width: 80 cm Depth: 9 cm Height: 23 cm
Weight:	6.48 kg
DMX channels:	7
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED type:	5 mm
LED number:	256
Beam angle:	15°

Mounting hole:	D = 36 mm
Dimensions (L x W x H):	800 x 90 x 230 mm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE LED SCY-200 Beam Effect

Power supply:	230 V AC, 50 Hz
Power consumption:	70 W
DMX channels:	20; 7
Control:	Sound to light via microphone
Fixtures available for:	Light´J
Beam angle (1/2 peak):	60°
Dimensions:	Width: 17.5 cm Depth: 37.5 cm Height: 15 cm
Weight:	2.40 kg
DMX channels:	20
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED type:	3 W TCL
LED number:	6
Beam angle:	60°
Dimensions (L x W x H):	175 x 375 x 150 mm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OMNITRONIC XLR Cable 3-pin 1m bk

Cable construction:	2 x 0.22 mm ² microphone cable
Cable length:	1 m
Plug A:	1 x 3-pin XLR (M)
Plug B:	1 x 3-pin XLR (F)
Color:	Black
Dimensions:	Diameter: Ø 0.60 cm
Weight:	0.10 kg
Material:	Metal

OMNITRONIC IEC Extension 3x0.75 1m bk

Cable construction:	3 x 0.75 mm ² power cable
Cable length:	1 m
Plug A:	1 x IEC (M)
Plug B:	1 x IEC (F)

Color:	Black
Weight:	0.11 kg

Scope of delivery:

1 x EUROLITE LED KLS-401 Compact Light Set

1 x spotlight

1 x EUROLITE STV-3529 Adapter long

1 x device
1 x user manual
2 x knurled screw

3 x OMNITRONIC IEC Extension 3x0.75 1m bk

1 x power cord