

## EUROLITE KLS-Kombo Pack 10

Universal mobile light set

Art. No.: 42109550

GTIN:



**The article is no longer in our assortment.**

### Features:

Universal mobile light set

- Combines four LED spots, a flower effect and a water effect
- The standard light system for every small band, solo entertainers and parties
- Set consisting of: 42109781 EUROLITE LED KLS-401 Compact lightset, 51918665 EUROLITE LED PIX-3 Flower effect, 2 x 51918612 EUROLITE LED MF-100 Flower effect, 60004120 Speaker system stand alu, black, 59007081 EUROLITE STV-3529 Adapter long
- Details to the products:
- KLS-401 Compact lightset
- Complete LED light set with 4 spots
- Compact and easy to transport
- 720 LEDs
- 4 IEC outputs for power supply of further devices
- LED PIX-3 Flower effect
- An angled row with 3 glass lenses offer phenomenal effects
- Operable in stand-alone mode or DMX interface
- Functions: Auto mode, sound control, internal programs, strobe settings via DMX, Master/Slave
- Equipped with 192 x 5 mm LED (48 x red, green, blue and white each)
- 51918612 EUROLITE LED MF-100 RGBAW flower effect
- Equipped with 5 x 3 W LED: 1 x red, 1 x green, 1 x blue, 1 x amber and 1 x white
- Available in three different models (flowereffekt with/without mirror, barrel effect)
- Functions: Static colors, colored beams in R, G, B, A and W, color change, color fade, strobe settings and motor-steps via DMX, Master/Slave
- You can find more information under the respective article

### Logistic

### **EUROLITE LED KLS-401 Compact Light Set**

Bar with 4 spots with 108 LEDs (RGB) each and carrying bag

- Complete LED light set with four slimline LED spots
- Crossbar with integrated DMX control unit
- Installation via TV pin for tripods with 28 mm interior diameter
- Ultra-light ideally suited for mobile use
- Comes pre-assembled with practical transport bag
- 180 x 10 mm LED per spot (60 x red, 60 x green, 60 x blue)
- Movable and tiltable spotlights
- DMX-controlled operation or stand-alone operation with processor-controlled color change
- Master/Slave operation
- Sound-control via built-in microphone with sensitivity control
- Convenient control possible via optional 4-pedal foot pedal FP-1 or IR remote control
- DMX512 control via regular DMX controller (occupies 15 channels)
- Optimized for control with the optional control panel DMX LED Operator 4
- Via DMX, each spot can be individually controlled
- DMX functions: dimmer, automatic mode, music control, strobe effect
- Addressing and setting via control panel with 4-digit LED display
- Suited for installation on a lighting stand (not included)
- Black lacquered metal version
- Ideal for bands, stages or solo entertainers
- Ready for connection with power cord and safety plug
- 4 IEC outputs for power supply of further devices
- 180 powerful LEDs 10 mm R/G/B<BR> spots controlled separately
- Control via stand-alone; DMX; Foot switch (optional); IR remote control (optional)
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- With a beam angle of 25°
- For further information about this product, please refer to the Data Sheet under "Downloads"

#### **Package contents**

- 1 x spotlight

### **OMNITRONIC Speaker System Stand alu bk**

High-quality speaker stand

- Stable speaker stand for mobile use
- The telescopic tube is additionally fixed with a safety pin
- Adjustable height

### **EUROLITE STV-3529 Adapter long**

Massive adapter for 35 mm tube, 28 mm TV spigot, maximum load WLL 100 kg

- For stands with telescopic tube 35 mm
- Connection element for cross beam with 28 mm TV spigot
- With M6 and M8 fixation screw
- Heavy version for highest stability
- TV spigot

#### **Package contents**

- 1 x device, 1 x user manual, 2 x knurled screw

### **EUROLITE LED PIX-3 Flower effect**

LED flower effect with 3 glass lenses for room-filling effects

- An angled row with 3 glass lenses offer phenomenal effects
- Operable in stand-alone mode or DMX interface
- DMX512 control possible via any commercial DMX controller (occupies max.3 channels)
- 2 or 3 DMX channels selectable for numerous applications
- Sound-control via built-in microphone
- Microphone sensitivity adjustable via rotary control
- Comfortable addressing and setting via control panel with LED display and four operating buttons
- Functions: Auto mode, sound control, internal programs, strobe settings via DMX, Master/Slave

- Equipped with 192 x 5 mm LED (48 x red, green, blue and white each)
- Locking possibility at the mounting bracket
- Including mounting bracket and mounting hole (36 mm) with fixation screw for installation on a truss system or stand
- Feed-through output allows to power another device
- After every 8 devices the fixtures must have a renewed connection with the power mains
- IEC Power cord with safety-plug included in delivery

### EUROLITE LED MF-100 Flower effect

RGBAW flower effect with 3 W LEDs

- Equipped with 5 x 3 W LED: 1 x red, 1 x green, 1 x blue, 1 x amber and 1 x white
- Available in three different models (flowereffekt with/without mirror, barrel effect)
- Functions: Static colors, colored beams in R, G, B, A and W, color change, color fade, strobe settings and motor-steps via DMX, Master/Slave
- DMX-controlled operation or stand-alone operation with Master/Slave function
- DMX512 control possible via any commercial DMX controller
- Comfortable addressing and setting via control panel with LED display and four operating buttons
- Sound-control via built-in microphone
- Microphone-sensitivity adjustable
- Manual focus
- Fuzzy sound control: program continues automatically during periods without music or bass-beat
- Easy installation

### OMNITRONIC XLR cable 3pin 0.5m bk

Audio cable with 3-pin XLR connectors<p class='attributgroup'>Package contents

- 1 x xLR cable

### Technical specifications:

Weight:	22,74 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

### EUROLITE LED KLS-401 Compact Light Set

Power supply:	230 V AC, 50 Hz
Power consumption:	55,00 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED:	180 x 10 mm R/G/B
DMX channels:	15
Control:	Stand-alone; DMX; Foot switch (optional); IR remote control (optional)

Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Beam angle:	25°
Beam angle (1/2 peak):	25°
Housing color:	Black
Dimensions:	Width: 1,2 m Depth: 5,5 cm Height: 31 cm
Weight:	9,30 kg
DMX connection:	3-pin XLR
LED type:	10 mm
LED number:	720 (240 red, 240 green, 240 blue)
TV spigot:	D = 28 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **OMNITRONIC Speaker System Stand alu bk**

Maximum carrying capacity:	30 kg
Height:	Maximum: 230 cm Minimum: 140 cm
Type (general stands):	Speaker stand/manual
Material:	Aluminum
Color:	Black
Weight:	3,45 kg
Maximum load:	30 kg
Maximum load (DIN15560):	18 kg
Minimum height:	1.40 m
Maximum height:	2.20 m

#### **EUROLITE STV-3529 Adapter long**

Maximum load BGV C1 (8-fold):	50 kg
Max. load WLL (4-fold):	100 kg
Attachment system:	TV spigot Ø 28mm Ø 35mm
Type (general stands):	Accessory
Material:	Steel, 6 mm, powder-coated
Dimensions:	Width: 8,50 cm Depth: 5 cm Height: 19,50 cm
Weight:	1,50 kg

#### **EUROLITE LED PIX-3 Flower effect**

Power supply:	230 V AC, 50 Hz
Power consumption:	20,00 W
Dimensions:	Width: 26,5 cm Depth: 38 cm Height: 19 cm
Weight:	3,55 kg
DMX channels:	2/3
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED type:	5 mm
LED number:	192
Beam angle:	80°
Mounting hole:	D = 36 mm
Dimensions:	265 x 380 x 190 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **EUROLITE LED MF-100 Flower effect**

Power supply:	230 V AC, 50 Hz
Power consumption:	25,00 W
Dimensions:	Width: 19,5 cm Depth: 20,5 cm Height: 26,5 cm
Weight:	2,35 kg
DMX channels:	3
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED type:	3 W
LED number:	5
Beam angle:	50°
Dimensions:	195 x 205 x 265 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **OMNITRONIC XLR cable 3pin 0.5m bk**

Cable construction:	Audio cable
Cable length:	0,5 m
Plug A:	1 x 3-pin XLR (M)
Plug B:	1 x 3-pin XLR (F)
Color:	Black
Weight:	80 g