

EUROLITE LED KLS-190 Compact Light Set

Bar with 4 RGB spots, 4 white strobe LEDs and QuickDMX USB port

Art. No.: 42109608 GTIN: 4026397657715











List price: 474.81 €

incl. 19% VAT.

Features:

- Crossbar with integrated DMX control unit and stand sleeve
- Compact lightweight
- Two additional frost filters provide a soft, homogeneous light
- Movable and tiltable spotlights
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- 19 integrated show programs
- Direct color selection for 18 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; Sound to light via Microphone; IR remote control; Master/slave function; standalone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- With a beam angle of 9°
- Preprogrammed in EASY SHOW 1; Light'J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3
- Silent operation
- Mains input and output for power linking up to 8 units
- Application possibility: On stand; suspended
- For application areas such as: Wedding/gala/events; Party room; mobile use; mobile djs / entertainer

spotlight

4 powerful LEDs 30 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
 spots controlled separately

bar

4 powerful LEDs 3 W high-power cold white (CW)
 LEDs controlled separately
Package contents

Logistic

EAN / GTIN: 4026397657715

Weight: 7,80 kg Length: 0.72 m Width: 0.23 m Heigth: 0.35 m 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 1 x bag, 8 x diffusor cover

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	60 W
IP classification:	IP20
Lamp type:	LED lamp
DMX channels:	4; 6; 7; 9; 13; 16
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; Sound to light via Microphone; IR remote control; Master/slave function; stand-alone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	EASY SHOW 1; Light'J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3
Beam angle:	9°
Beam angle (1/2 peak):	9°
	42°
Beam angle (1/10 peak):	20°
	72°
Housing color:	Black
Dimensions:	Width: 66,0 cm
	Depth: 15,0 cm Height: 26,5 cm
	6,29 kg
Noise classification:	· •
	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Spotlight	
LED:	4 x 30 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
Bar	
LED:	4 x 3 W high-power cold white (CW)
Legal specifications	
Special product:	Not designed for household room illumination