

EUROLITE LED KLS-170 Compact Light Set

Bar with 4 RGB spots, cold white + UV strobe LEDs, foot switch and carrying bag

Art. No.: 42109620

GTIN: 4026397582611



The article is no longer in our assortment.

Features:

- Compact lightweight
- Crossbar with integrated DMX control unit and stand sleeve
- 31 integrated show programs
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; wireless footswitch; IR remote control; sound to light via microphone; master/slave function
- Preprogrammed in EASY SHOW 1; Light´J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3
- With a beam angle of 13°
- With mounting bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Party room; mobile use; mobile djs / entertainer; small rental
- Silent operation
- Application possibility: On stand
- spotlight**
- 3 powerful LEDs 9 W SMD 8072 3in1 TCL RGB (homogenous color mix)
 spots controlled separately
- bar**
- 4 powerful LEDs 2 W high-power 2in1 BCL CW/UV (homogenous color mix)
 LEDs controlled separately
- Package contents**
- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x bag, 1 x foot control, 1 x remote control, 2 x battery, 2 x mounting bracket, 2 x knurled screw, 2 x washer

Logistic

EAN / GTIN: 4026397582611

Weight: 7,80 kg

Length: 1.07 m

Width: 0.29 m

Heigh: 0.16 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	90 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Lamp type:	LED lamp
DMX channels:	3; 6; 16; 25
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; wireless footswitch; IR remote control; sound to light via microphone; master/slave function
Preprogrammed in:	EASY SHOW 1; Light´J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3
Beam angle:	13°
Beam angle (1/2 peak):	13°
Beam angle (1/10 peak):	25°
Housing color:	Black
Attachment system:	2x mounting bracket
Dimensions:	Width: 103 cm Depth: 55 cm Height: 24 cm
Weight:	6,25 kg
Noise classification:	Class 0 (no noise at all)
Spotlight	
LED type:	3 x 9 W SMD 8072 3in1 TCL RGB (homogenous color mix)
Foot control	
Battery:	1 x 9.0 V E block 6F22 zinc carbon included
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Bar	
LED type:	4 x 2 W high-power 2in1 BCL CW/UV (homogenous color mix)
Flash rate:	0 - 30 Hz
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting